



**NOTES:**

1. RoHS COMPLIANT
- (b) 2. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
3. INSULATOR: HIGH TEMPERATURE PLASTIC UL 94 V-0, BLACK
- (c) 4. CONTACTS: COPPER ALLOY; PLATING (SEE PART NO.):
  - PLEASE ADD A for GOLD FLASH over NICKEL (PREFERRED TYPE)
  - PLEASE ADD B for 20µin HARD GOLD over min. 50µin NICKEL
  - PLEASE ADD C for 30µin HARD GOLD over min. 50µin NICKEL
5. SEALING COMPOUND: PUR; BLUE
6. CAPACITANCE: 180pF ± 20%
7. DIELECTRIC WITHSTANDING VOLTAGE: 424 VDC
8. CONNECTOR IS PART MARKED: **241□26860X CONEC ABC**

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm		scale: 2:1 (5:1)	
					material: SEE NOTES	
			date		title:	
			name		D-SUB FILTER MALE 25pos. SOLDER CUP	
			drawn 30.06.09 Petker			
		appd. 01.07.09 Fischer		dwg no:		
		norm		24K1A1183		
3 x c		Ä4494	09.10.2012	K.H.	d-old	DIN-A3
1 x b		Ä 3387	15.07.2009	Petker		sh: 1
a		Origin				
rev.		description	date	name	part no: (c) 241□26860X (see note 3)	

**CONEC**®