

## Field bus components FBCon PA CG 2way OVP

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



The FBCon Fieldbus distributor is available in the industry and EEx (ia) version. They are used for coupling from 1 to 8 field devices or sensors.

They are connected via spur lines. The connection to the spur line can be made with an M12 plug or directly via an EMC cable gland. Communication and device power feed are transferred by a common 2-wire line.

The distributors offer the following features respective of the version:

- Tension-clamp connection system
- Overvoltage protection for the main line
- Current limiter for each branch line
- EMC cable gland
- M12 plug-in connectors
- External earthing contact
- Interruption-free bus operation
- Industrial version
- Bus termination integrated (not EX)
- ATEX explosion-proof version
- Pressure-equalising element
- Protection degrees IP65, IP66, IP67
- Stainless steel versions
- PROFIBUS-PA compatible

### General ordering data

Type	FBCon PA CG 2way OVP
Order No.	<a href="#">8714130000</a>
Version	Standard distributor with surge protection, 2-channel distributor OVP, IP 66
GTIN (EAN)	4032248398195
Qty.	1 pc(s).

## Data sheet

### Field bus components FBCon PA CG 2way OVP

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

Length	98 mm	Width	64 mm
Height	36 mm	Net weight	362 g

### Temperatures

Operating temperature	-40 °C...+80 °C	Storage temperature	-40 °C...+80 °C
-----------------------	-----------------	---------------------	-----------------

### Technical data

Cable gland	branch line CG	Colour	Grey
Connection type PE	Spur line with cable gland	Protection degree	IP 66
Type of mounting	surface-mounted	Version	Aluminium enclosure

### Classifications

ETIM 3.0	EC000214	UNSPSC	26-12-16-03
eClass 5.1	27-25-02-01	eClass 6.2	27-24-26-08
eClass 7.1	27-24-26-08		

### Product information

Descriptive text ordering data	CG = brass cable gland PCG = plastic cable gland
Descriptive text technical data	FBcon products cannot be used in strongly saline environment.

### Approvals

Approvals	
ROHS	Conform

### Downloads

Declaration of Conformity	<a href="#">K328_01_10.pdf</a>
---------------------------	--------------------------------