

FLARE-MAXI

34 x 33 mm lens with ~100° x 15° oval beam

SPECIFICATION:

Dimensions	33.9 x 33.3 mm
Height	16.7 mm
Fastening	glue, pin
ROHS compliant	yes ⓘ




MATERIALS:

Component	Type	Material	Colour	Finish
FLARE-MAXI	Single lens	PMMA	clear	

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C12868_FLARE-MAXI » Box size:	840	168	168	9.5




See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):


CREE LED

LED XHP70.2
 FWHM / FWTM 105.0 + 28.0° / 153.0 + 38.0°
 Efficiency 94 %
 Peak intensity 1.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




CREE LED

LED XM-L
 FWHM / FWTM 96.0 + 15.0° / 147.0 + 28.0°
 Efficiency 94 %
 Peak intensity 2.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




CREE LED

LED XM-L2
 FWHM / FWTM 95.0 + 14.0° / 145.0 + 18.0°
 Efficiency 94 %
 Peak intensity 2.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



CREE LED


LED XP-E
 FWHM / FWTM 94.0 + 6.0° / 149.0 + 10.0°
 Efficiency 94 %
 Peak intensity 4.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (MEASURED):


CREE LED

LED XP-E2
 FWHM / FWTM 91.0 + 6.0° / 146.0 + 10.0°
 Efficiency 94 %
 Peak intensity 4.8 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:




CREE LED

LED XP-G
 FWHM / FWTM 105.0 + 11.0° / 152.0 + 22.0°
 Efficiency 94 %
 Peak intensity 2.5 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:





CREE LED

LED XP-G2
 FWHM / FWTM 96.0 + 10.0° / 147.0 + 15.0°
 Efficiency 94 %
 Peak intensity 3.1 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:



CREE LED


LED XP-L HD
 FWHM / FWTM 115.0 + 13.0° / 149.0 + 19.0°
 Efficiency 94 %
 Peak intensity 2.1 cd/m
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (MEASURED):



CREE LED

LED XT-E
 FWHM / FWTM 96.0 + 10.0° / 160.0 + 23.0°
 Efficiency 94 %
 Peak intensity 2.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LUMILEDS

LED LUXEON M/MX
 FWHM / FWTM 100.0 + 23.0° / 147.0 + 36.0°
 Efficiency 94 %
 Peak intensity 1.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LUMILEDS

LED LUXEON Rebel ES
 FWHM / FWTM 91.0 + 10.0° / 144.0 + 20.0°
 Efficiency 94 %
 Peak intensity 2.8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:











LUMILEDS

LED LUXEON T
 FWHM / FWTM 96.0 + 10.0° / 147.0 + 115.0°
 Efficiency 92 %
 Peak intensity 2.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





OPTICAL RESULTS (MEASURED):

<p>LUMILEDS</p> <p>LED LUXEON TX</p> <p>FWHM / FWTM 96.0 + 9.0° / 141.0 + 14.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 3.2 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p>NICHIA</p> <p>LED NCSxx19B</p> <p>FWHM / FWTM 98.0 + 9.0° / 155.0 + 15.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 3.5 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p>NICHIA</p> <p>LED NV4x144A</p> <p>FWHM / FWTM 108.0 + 19.0° / 157.0 + 27.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 1.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p>NICHIA</p> <p>LED NVSxx19B/NVSxx19C</p> <p>FWHM / FWTM 98.0 + 11.0° / 153.0 + 23.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 2.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		


OPTICAL RESULTS (MEASURED):





LED NWSx229A
FWHM / FWTM 122.0 + 13.0° / 147.0 + 20.0°
Efficiency 94 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED OSOLON Square PC
FWHM / FWTM 98.0 + 13.0° / 153.0 + 25.0°
Efficiency 94 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED LH351Z
FWHM / FWTM 95.0 + 9.0° / 125.0 + 13.0°
Efficiency 94 %
Peak intensity 3.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OPTICAL RESULTS (SIMULATED):


CREE LED

LED XD16
 FWHM / FWTM 60.0 + 7.0° / 143.0 + 13.0°
 Efficiency 94 %
 Peak intensity 3.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




CREE LED

LED XHP50.3 HD
 FWHM / FWTM 92.0 + 20.0° / 139.0 + 28.0°
 Efficiency 95 %
 Peak intensity 1.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




CREE LED

LED XHP70.3 HI
 FWHM / FWTM 86.0 + 18.0° / 141.0 + 29.0°
 Efficiency 96 %
 Peak intensity 1.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:







CREE LED






LED XP-G2 HE
 FWHM / FWTM 75.0 + 11.0° / 137.0 + 18.0°
 Efficiency 95 %
 Peak intensity 2.8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (SIMULATED):

<p>LUMILEDS</p> <p>LED LUXEON 7070</p> <p>FWHM / FWTM 92.0 + 25.0° / 146.0 + 100.0°</p> <p>Efficiency 96 %</p> <p>Peak intensity 1.3 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	
<p>LUMILEDS</p> <p>LED LUXEON H50-2</p> <p>FWHM / FWTM 9.5 + 64.0° / 15.0 + 122.0°</p> <p>Efficiency 92 %</p> <p>Peak intensity 3.6 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	
<p>LUMILEDS</p> <p>LED LUXEON V</p> <p>FWHM / FWTM 12.0 + 79.0° / 23.0 + 143.0°</p> <p>Efficiency 93 %</p> <p>Peak intensity 2.2 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	
<p>NICHIA</p> <p>LED NVSW219D</p> <p>FWHM / FWTM 85.0 + 12.0° / 127.0 + 21.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 2.7 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	


OPTICAL RESULTS (SIMULATED):

<p>NICHIA</p> <p>LED: NVSW3x9A</p> <p>FWHM / FWTM: 95.0 + 12.0° / 144.0 + 22.0°</p> <p>Efficiency: 94 %</p> <p>Peak intensity: 2.3 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>		
<p>OSRAM Opto Semiconductors</p> <p>LED: OSCONIQ P 3737 (3W version)</p> <p>FWHM / FWTM: 69.0 + 12.0° / 133.0 + 20.0°</p> <p>Efficiency: 95 %</p> <p>Peak intensity: 2.7 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>		
<p>OSRAM Opto Semiconductors</p> <p>LED: OSCONIQ P 7070</p> <p>FWHM / FWTM: 84.0 + 18.0° / 140.0 + 23.0°</p> <p>Efficiency: 93 %</p> <p>Peak intensity: 1.8 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	 <p>detector size: 1.5x1.5mm</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED: OSOLON SSL 80</p> <p>FWHM / FWTM: 46.0 + 6.0° / 101.0 + 12.0°</p> <p>Efficiency: 95 %</p> <p>Peak intensity: 5.7 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>		

OPTICAL RESULTS (SIMULATED):


SAMSUNG

LED LH351B
 FWHM / FWTM 68.0 + 10.0° / 126.0 + 17.0°
 Efficiency 94 %
 Peak intensity 3.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




SAMSUNG

LED LH351C
 FWHM / FWTM 74.0 + 11.0° / 126.0 + 20.0°
 Efficiency 94 %
 Peak intensity 2.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



SAMSUNG

LED LH502C
 FWHM / FWTM 93.0 + 18.0° / 140.0 + 27.0°
 Efficiency 95 %
 Peak intensity 1.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)