

circular Connector w. Harax M12 L5 M



Image is for illustration purposes only. Please refer to product description.

| | |
|---------------|--------------------------------------|
| Part number | 21 03 271 1505 |
| Specification | circular Connector w. Harax M12 L5 M |

Identification

| | |
|----------------|-------------------------|
| Category | Connectors |
| Series | Circular connectors M12 |
| Identification | M12-L |
| Element | Cable connector |
| Specification | Straight |

Version

| | |
|--------------------|--|
| Termination method | HARAX [®] connection technology |
| Gender | Male |
| Shielding | Unshielded |
| Number of contacts | 5 |
| Coding | A-coding |
| Locking type | Screw locking |

Technical characteristics

| | |
|-------------------------|-------------------------------|
| Conductor cross-section | 0.25 ... 0.34 mm ² |
| Conductor cross-section | AWG 24 ... AWG 22 |
| Wire outer diameter | ≤2 mm |
| Rated current | 4 A |
| Rated voltage | 50 V |
| Rated impulse voltage | 1.5 kV |
| Pollution degree | 3 |
| Overvoltage category | III |



Technical characteristics

| | |
|---|-----------------------------|
| Insulation resistance | >10 ⁸ Ω |
| Contact resistance | ≤10 mΩ |
| Tightening torque | 0.6 Nm |
| Wrench size (knurled screw / knurled nut) | 17 |
| Limiting temperature | -40 ... +85 °C |
| Mating cycles | ≥100 |
| Degree of protection acc. to IEC 60529 | IP65 / IP67 mated condition |
| Cable diameter | 4.7 ... 6 mm |
| Isolation group | I (600 ≤ CTI) |

Material properties

| | |
|--------------------------------------|---------------------------------|
| Material (insert) | Polyamide (PA) |
| Material (contacts) | Brass |
| Surface (contacts) | Au over Ni Mating side |
| Material (hood/housing) | Polyamide (PA) Zinc die-cast |
| RoHS | compliant with exemption |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| California Proposition 65 substances | Yes |

Specifications and approvals

| | |
|----------------|--|
| Specifications | IEC 61076-2-101 |
| UL / CSA | UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079 |

Commercial data

| | |
|--------------------------------|---------------|
| Packaging size | 1 |
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| GTIN | 5713140137424 |

Product data sheet
21 03 271 1505
circular Connector w. Harax M12 L5 M

This product is not orderable anymore. Please contact your local distribution partner.



Pushing Performance
Since 1945

Commercial data

eCl@ss

27440116 Circular connector (for field assembly)