



- NOTES: (c) (d) (e)
- HOOD: PBT GF UL 94 V0, BLACK
TEMPERATURE RANGE -30°C TO +90°C
 - PG-GLAND: PA UL 94 V0
TEMPERATURE RANGE -30°C TO +90°C
 - FRONTSEALING: TPE UL 94 V0
TEMPERATURE RANGE -30°C TO +90°C
 - O-RING FOR PG-GLAND: NBR
TEMPERATURE RANGE -30°C TO +90°C
 - JACK SCREWS: STAINLESS STEEL
RECOMMENDED TORQUE: 30Ncm
 - WASHER: STAINLESS STEEL
 - O-RING FOR JACK SCREWS: NBR
TEMPERATURE RANGE -30°C TO +90°C

Shell-size	A	B	C	φD	E	F	G ^{±1}	H	RECOMMENDED TORQUE FOR PG-GLAND	Cable φ	Part NO.
1	40.76	25.0	SW 22	24.6	51.0	22.0	77.0	44.0	3.0 Nm	5 - 10	165X14819X
2	49.06	33.3	SW 24	26.5	51.0	22.0	79.0	52.0	4.5 Nm	6 - 12	165X14829X
3	62.80	47.04	SW 24	26.5	59.5	22.0	87.5	52.0	4.5 Nm	6 - 12	165X14839X
4	78.86	63.5	SW 33	36.2	67.0	22.0	99.0	52.0	4.0 Nm	9 - 16	165X14849X
5	76.46	61.1	SW 42	47.0	67.0	24.8	107.0	52.0	6.0 Nm	13 - 20	165X14859X

25-50pos.

tolerance

dim. in mm

scale: 1:1

material: SEE NOTES

title: WATER RESISTANT D-SUB HOOD
9-50pos.
with jack screw 4-40 UNC

dwg no: 16K1A489

part no: SEE TABLE

DIN-A 3 sh: 1/1

2002 date name
drawn 13.02. Parei
appd. 13.02. E.Mickenbecker

2 x e Ä4303 08.05.2012 K.H.
3 x d Ä3678 24.06.2010 Petker
1 x c Ä3141 13.10.2008 Sonne
2 x b Ä1741 26.02.2003 Parei

rev. description date name

DO NOT ALTER CAD DRAWING BY HAND

OWNERSHIP AND COPYRIGHT OF CONEC GmbH

WRITTEN PERMISSION.
BE PASSED ON TO A THIRD PARTY WITHOUT

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT

Directive 2002/95/EC RoHS compliant