


Data sheet | Item number: 289-179

Interface module; RJ-45; with power jumper contacts; PCB terminal blocks, double-row; Cat. 5; in mounting carrier; with shield connection; with shield clamping saddle; 1,50 mm²

www.wago.com/289-179



Data

Electrical data

Operating voltage	≤35 VAC; ≤50 VDC
Nominal current	2.1 A
Insulation resistance	≥ 500 MΩ
Specialty functions	With power jumper contacts with shield connection

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



With shield clamping saddle

Safety and protection

Dielectric strength (contact/contact) (AC, 1 min)	1 kV _{rms}
---	---------------------

Connection data

Mating cycles	1,000
Transmission length (max.)	100 m
Connection cable	Cat. 5 (min.)
WAGO shield clamping saddle	11 mm wide; cable diameter up to 8 mm

Connection 1

Connector	RJ-45 (shielded); with two additional power contacts
Pole number 1	10
Connection type 1	System

Connection 2

Design 2	PCB terminal blocks (double-row)
Pole number 2	11
Connection type 2	System
Connection technology 2	CAGE CLAMP®
WAGO connector 2	WAGO 739 Series
Solid conductor 2	0.08 ... 1.5 mm ² / 28 ... 14 AWG
Fine-stranded conductor 2	0.08 ... 1.5 mm ² / 28 ... 14 AWG
Strip length 2	5 ... 6 mm / 0.2 ... 0.24 inches

Physical data

Width	30 mm / 1.181 inches
Height	85 mm / 3.346 inches
Depth from upper-edge of DIN-rail	67 mm / 2.638 inches

Mechanical Data

Mounting type	DIN-35 rail
Housing design	Mounting carrier
Mating cycles	1,000

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.



Material Data

Fire load	0.83 MJ
Weight	52.5 g

Environmental requirements

Ambient temperature (operation)	-40 ... +85 °C (Actuation: -35 ... +85 °C)
Ambient temperature (storage)	-40 ... +85 °C
Relative humidity	85% (non-condensing)

Commercial data

Product Group	6 (INTERFACE ELECTRONIC)
eCl@ss 10.0	19-17-90-01
eCl@ss 9.0	19-17-90-01
ETIM 8.0	EC001121
ETIM 7.0	EC001121
Recupel Type	
PU (SPU)	10 (1) pcs
Packaging type	box
Country of origin	DE
GTIN	4045454326197
Customs tariff number	85366990990

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Optional accessories

Tool

Operating tool		
Item no.: 210-719		
Operating tool; Blade: 2.5 x 0.4 mm; with a partially insulated shaft		www.wago.com/210-719

Marking accessories

Marking strip		
Item no.: 709-196		
Marking strips; for laser printer; translucent		www.wago.com/709-196
Item no.: 709-178		
Marking strips; on reel; 7.5 mm wide; not stretchable; plain; snap-on type; white		www.wago.com/709-178

Subject to changes. Please also observe the further product documentation!

Item no.: 709-177

Marking strips; on reel; 7.5 mm wide; not stretchable; plain; snap-on type; translucent

www.wago.com/709-177

Downloads

Documentation

Bid Text

289-179 X81 - Datei	2019 年2月19日	xml 3.9 kB	Download
------------------------	-------------	---------------	----------

289-179 doc - Datei	2015 年2月9日	doc 26.6 kB	Download
------------------------	------------	----------------	----------

Instruction Leaflet

		pdf 1.3 MB	Download
--	--	---------------	----------

Additional Information

Disposal and Recycling Electrical and electronic equipment, Batteries, Packaging	V 1.1.0 2022 年8月18日	pdf 2.2 MB	Download
---	------------------------	---------------	----------

CAD/CAE-Data

CAD data

2D/3D Models 289-179		URL	Download
----------------------	--	-----	----------

CAE data

WSCAD Universe 289-179		URL	Download
------------------------	--	-----	----------

ZUKEN Portal 289-179		URL	Download
----------------------	--	-----	----------

EPLAN Data Portal 289-179		URL	Download
---------------------------	--	-----	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 289-179		URL	Download
--	--	-----	----------

Subject to changes. Please also observe the further product documentation!



Interface module; RJ-45; with power jumper contacts; PCB terminal blocks, double-row; Cat. 5; in mounting carrier; with shield connection; with shield clamping saddle; 1,50 mm²

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.