

NOTES:

General Note:

1. All assemblies must be 100% tested for VSWR
2. No component substitutions are permitted

Mechanical Note:

1. Overall Height: 84 mm from G.P.
2. Weight: 3.7 oz
3. IP Rating: IP67
4. Operating temp: -30C to +80C
5. Color: Black
6. Mounting: NMO
7. Installation Torque: 4 - 6 ft*lbs



Electrical Note:

1. Frequency Range: 806 - 896 MHz; 1850 - 1990 MHz; 2500 - 2700 MHz
2. VSWR: ≤2:1
3. Nominal Impedance: 50 OHM
4. Gain (dBi): 3 dBi
5. Polarization: Vertical
6. Pattern: Omnidirectional
7. Ground Plane: Tested on 2' x 2' G.P.

Packaging Note:

1. TE Part Number: TRA8063M3NB-001
2. Package: S1136
3. Units per Package: 1
4. Package Label: Printed Bag
5. Box: N/A
6. Units per Box: N/A
7. Box Label: N/A

REVISIONS					
ZONE	REV.	DESCRIPTION	DATE	DRAWN BY	ECR NUMBER
	A	Initial Release	1/26/2012	BPH	N/A



High Strength Impact Resistant ABS Radome

Rugged Insert Molded Design

O-ring must be in place during installation and must get full compression on the ground plane or surface



MATERIAL: N/A		THIRD ANGLE PROJECTION		
FINISH: N/A		INTERPRET DIMENSIONING AND TOLERANCING IN ACCORDANCE WITH ASME Y14.5M-1994		
APPROVALS	DATE	DO NOT SCALE DRAWING		TITLE: OMNI, Ph, 806/1850/2500 MHz, 3 dBi, 100W, NMO
ME: <i>BPH</i>		TOLERANCES UNLESS OTHERWISE SPECIFIED		
RF: <i>###</i>		DIMENSIONS ARE IN MILLIMETERS		SIZE DWG NO.
EM:		ANGLE: 0 PLACE DECIMAL: ±30° 1 PLACE DECIMAL: ±0.5 2 PLACE DECIMAL: ±0.13		A2
Prod:				TRA8063M3NB-001 - MO
WEIGHT:		PREVIOUS#		SCALE:
				SHEET 1 OF 1

THIS DRAWING IS UNPUBLISHED.	RELEASED FOR PUBLICATION	-,-
© Copyright 2022 TE Connectivity Ltd.		ALL RIGHTS RESERVED.