


✓ 54/7402 011098
 ✓ 54S/74S02 011105
 ✓ 54LS/74LS02 011103
 QUAD 2-INPUT NOR GATE

CONNECTION DIAGRAMS
 PINOUT A




4

ORDERING CODE: See Section 9

PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		$V_{CC} = +5.0\text{ V} \pm 5\%$, $T_A = 0^\circ\text{ C to } +70^\circ\text{ C}$	$V_{CC} = +5.0\text{ V} \pm 10\%$, $T_A = -55^\circ\text{ C to } +125^\circ\text{ C}$	
Plastic DIP (P)	A	7402PC, 74LS02PC 74S02PC		9A
Ceramic DIP (D)	A	7402DC, 74LS02DC 74S02DC	5402DM, 54LS02DM 54S02DM	6A
Flatpak (F)	A	74LS02FC, 74S02FC	54LS02FM, 54S02FM	3I
	B	7402FC	5402FM	

PINOUT B



INPUT LOADING/FAN-OUT: See Section 3 for U.L. definitions

PINS	54/74 (U.L.) HIGH/LOW	54/74S (U.L.) HIGH/LOW	54/74LS (U.L.) HIGH/LOW
Inputs	1.0/1.0	1.25/1.25	0.5/0.25
Outputs	20/10	25/12.5	10/5.0 (2.5)

DC AND AC CHARACTERISTICS: See Section 3*

SYMBOL	PARAMETER	54/74		54/74S		54/74LS		UNITS	CONDITIONS	
		Min	Max	Min	Max	Min	Max		$V_{IN} = \text{Gnd}$	$V_{CC} = \text{Max}$
I_{CCH}	Power Supply Current	16		29		3.2		mA		
I_{CCL}		27		45		5.4			$V_{IN} = \text{Open}$	
t_{PLH}	Propagation Delay	15	2.0	5.5		10		ns	Figs. 3-1, 3-4	
t_{PHL}		15	2.0	5.5		10				

*DC limits apply over operating temperature range; AC limits apply at $T_A = +25^\circ\text{ C}$ and $V_{CC} = +5.0\text{ V}$.