## HDC enclosures HDC HB 24 TEK TSS1xM40G



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





The new RockStar® enclosures are resistant to seawater and offer a high degree of shock resistance, meet IP 68 and IP 69K, and have been developed for use under extreme environmental conditions and designed for the high vibration requirements acc. to DIN EN 61373 cat. 2 (bogie). As such, this housing family is ideally suited for fault- and maintenance-free operation of heavy-duty connectors in transport and traffic engineering as well as in power engineering and in applications with extreme requirements. During development, measures were also implemented to make the enclosures extremely EMCresistant.

#### General ordering data

Order No.	<u>1000920001</u>	
Туре	HDC HB 24 TEK TSS1xM40G	
Version	HDC enclosures, Size: 8, Protection degree: IP 68, Plug housing, Screw plug, high, Size of cable entries: M 40	
GTIN (EAN)	4032248691708	
Qty.	1 pc(s).	

## HDC enclosures HDC HB 24 TEK TSS1xM40G

# **Technical data**

.




### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Dimensions and weights				
Length	184 mm	Width	58 mm	
Height	120 mm	Net weight	755 g	
Temperatures				
Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	125 °C	
Dimensions				
Total length housing	184 mm	Width housing C	58 mm	
Height of housing B	120 mm	Cable entry	w. threading	
General data				
Housing main material	diecast aluminium			
Version				
Design of hereing	Dhua hausia a	Ci	0	
Design of housing	Plug housing	Size	8	
Design Design of locking system	high Screw plug	Top part/bottom part/lid Cable entry	upper part w. threading	
Size of cable entries	M 40	Number of cable entry on top	0	
Number of cable entry sideways	1		0	
Classifications				
ETIM 2.0	EC000437	ETIM 3.0	EC000437	
UNSPSC	30-21-18-01	eClass 4.1	27-14-08-05	
eClass 5.1	27-14-34-19	eClass 6.2	27-26-12-04	
eClass 7.1	27-44-02-05			
Approvals				
Approvals				
ROHS	Conform			

## HDC enclosures HDC HB 24 TEK TSS1xM40G

# Drawings





### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com