SIEMENS

Data sheet

US2:52BP2GT



30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Illuminated Push-Pull Operator Transformer type, 120V AC Incandescent Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Plastic, Amber 2 Position Maintained, Pull-to-Release UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

design of the product	Actuator round	
Enclosure		
number of command points	1	
delivery state as a kit	No	
Actuator		
product extension optional light source	Yes	
color of the actuating element	amber	
material of the actuating element	plastic	
type of unlocking device	pull-to-unlatch mechanism	
number of switching positions	2	
Front ring		
product component front ring	Yes	
design of the front ring	standard	
material of the front ring	metal	
color of the front ring	black	
Holder		
material of the holder	Metal	
Contact block/ lampholder		
socket design	BA 9s with lamp	
number of lampholders	1	
Display		
number of LED modules	0	
General technical data		
product component		
lamp transformer	Yes	
light source	Yes	
degree of pollution	1	
type of voltage		
 of the operating voltage 	AC	
 of the input voltage 	AC	
surge voltage resistance rated value	4 kV	
protection class IP	IP66	
• of the terminal	IP20	
Supply voltage		
type of voltage of the supply voltage of the light source	AC	
supply voltage of the light source at AC at 60 Hz		
• rated value	6 V	
Inputs/ Outputs		
output voltage 1 of the lamp transformer rated value	6 V	
Connections/ Terminals		

be of electrical connection	screw-type terminals
 of modules and accessories 	Screw-type terminal
htening torque of the screws in the bracket	20 N·m
ntening torque [lbf·in] with screw-type terminals	8 8 lbf-in
р	
be of light source	filament lamp
lor of the light source	clear
Safety related data	
uch protection against electrical shock	finger-safe
ient conditions	
ibient temperature	
during operation	-35 +70 °C
during storage	-40 +85 °C
allation/ mounting/ dimensions	
ape of the installation opening	round
ificates/ approvals	
her information	
Siemens has decided to exit the Russian market (see here).	
ps://press.siemens.com/global/en/pressrelease/siemens-wind	
Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an	
EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).	
Information on the packaging	
https://support.industry.siemens.com/cs/ww/en/view/109813875	
Information- and Downloadcenter (Catalogs, Brochures,)	
ps://www.siemens.com/ic10	
lustry Mall (Online ordering system)	
	lfb=US2:52BP2GT
ps://mall.industry.siemens.com/mall/en/en/Catalog/product?m x online generator	Ifb=US2:52BP2GT
ps://mall.industry.siemens.com/mall/en/en/Catalog/product?m	
ps://mall.industry.siemens.com/mall/en/en/Catalog/product?m x online generator p://support.automation.siemens.com/WW/CAXorder/default.a rvice&Support (Manuals, Certificates, Characteristics, FA	spx?lang=en&mlfb=US2:52BP2GT Qs,)
ps://mall.industry.siemens.com/mall/en/en/Catalog/product?m x online generator p://support.automation.siemens.com/WW/CAXorder/default.a rvice&Support (Manuals, Certificates, Characteristics, FA ps://support.industry.siemens.com/cs/ww/en/ps/US2:52BP2G	spx?lang=en&mlfb=US2:52BP2GT Qs,) I
ps://mall.industry.siemens.com/mall/en/en/Catalog/product?m x online generator p://support.automation.siemens.com/WW/CAXorder/default.a rvice&Support (Manuals, Certificates, Characteristics, FA	spx?lang=en&mlfb=US2:52BP2GT Qs,) I D models, device circuit diagrams, EPLAN macros,)

last modified:

5/31/2021 🖸