



TECHNICAL LISTED:

RATED SUPPLY VOLTAGE:	120VAC	UL & CSA
RATED CURRENT:	UP TO 15 AMPS	
RESET TYPE:	MANUAL	
OPERATING FREQUENCY:	60 Hz	
TYPE:	CLASS A	
GROUND TRIP CURRENT:	4-6 mA	
OVERLOAD CURRENT:	90 AMP 125 VAC	
INSULATION VOLTAGE:	1,500 VRMS - 1 MINUTE	
ENDURANCE OPERATIONS:	3000 OPERATIONS	
GFCI ENCLOSURE:	NEMA 3R	

MATERIAL NUMBER	ENGINEERING NUMBER	CORD TYPE	LENGTH "L"
1301530071	15053-2	12/3 SOOW	2 FT. ± 1 IN.
1301530072	15053-25	12/3 SOOW	25 FT. ± 2 IN.
1301530077	15053-50	12/3 SOOW	50 FT. ± 4 IN.

FUNCTIONAL SYMBOLS $\nabla_A = 0$ $\nabla_C = 0$ $\nabla_P = 0$	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: NEW SALES DRAWING CREATED							
	DIMENSION UNITS	SCALE								
	INCH	NTS								
	GENERAL TOLERANCES (UNLESS SPECIFIED)									
DIVISIONAL SYMBOLS 4 PLACES ± 3 PLACES ± 2 PLACES ± 1 PLACE ± 0 PLACES ±	ANGULAR TOL ± °	EC NO: 686059	GFCI 15A ATTACHABLE WITH DUAL SIDE OUTLET BOX							
	DRWN: PPURSUTANDEL	2021/11/02	PRODUCT CUSTOMER DRAWING							
	CHK'D: DNGUYEN62	2021/12/01	DOCUMENT NUMBER							
	APPR: HKNEELAND	2022/01/04	1301530071							
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER	DOC TYPE	DOC PART	REVISION	SHEET NUMBER
			C-SIZE	130153	SEE TABLE	GENERAL MARKET	PSD	000	A	1 OF 1