



NOTES:
 MATERIAL:
 HOOD: POLYAMID 6.6 GF 25 UL 94 V-0; BLACK
 SCREW: COPPER ALLOY; NICKEL PLATED
 CLAMP: STEEL; NICKEL PLATED

NO. OF POS.	A	B	C	D	PART NO.
9	31.2	25.0	22.8	8.0	165X13179X
25	53.5	47.0	44.8	10.3	165X13199X
37	69.7	63.5	61.3	10.3	165X13209X

used for: D-SUB

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.
 OWNERSHIP AND COPYRIGHT OF CONEC GMBH DO NOT ALTER CAD DRAWING BY HAND

rev.	description	date	name
01	A 5-7	13.12.94	Bar.

tolerance: ±0.3
 scale: 2:1
 material: SEE NOTES

1994	date	name
drawn	23.03.	Barcinski
appd.	23.03.	Mickenbecker
norm	DIN 41652	
d-old	16V1100A	

title: TWO-PART HOOD
 9, 25 and 37pos. FOR CABLE BINDING
 FLAT VERSION
 dwg no: AutoCADREL.13 DIN-A
 3
 ish: 1/1
 part no: SEE TABLE

