

2404177

https://www.phoenixcontact.com/us/products/2404177

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Maintenance license (5 years) for SUP-0 Emalytics Supervisor license

Commercial data

Item number	2404177
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	DR18
Product key	DRHBAA
GTIN	4055626349275
Weight per piece (including packing)	0.001 MGM
Weight per piece (excluding packing)	0.001 MGM
Customs tariff number	49119900
Country of origin	US

2404177

https://www.phoenixcontact.com/us/products/2404177

Technical data

Product properties				
Product type	Building management system			
Area of application	Building technology			
System properties				
Type of software	On-premise			
Intended use for the software	Automation			
	Engineering			
License information				
Type of license	Maintenance license			
License duration	5 Jahre			
Functionality				
Integrated function	Analysis			
	Data acquisition			
	Diagnostics			
	Startup			
	Communication			
	Configuration			
	Project planning			
	Simulation			
Target system	Server			
Supported controllers	ILC 2050 BI			
Number of data points	not relevant			
Number of clients	0			
System requirements				
Languages supported	German, English			
Screen resolution	1024 x 768 pixel(s) ,or higher			

PHŒNIX CONTACT

2404177

https://www.phoenixcontact.com/us/products/2404177



Classifications

ECLASS

ECLASS-11.0	27242590
ECLASS-12.0	27242590
ECLASS-13.0	27242590

ETIM

	ETIM 8.0	EC001435	
UNSPSC			
	UNSPSC 21.0	43233600	

2404177

https://www.phoenixcontact.com/us/products/2404177



Accessories

ILC 2050 BI - Controller

2403160 https://www.phoenixcontact.com/us/products/2403160



Modular Inline controller for automation applications in the fields of building technology, infrastructure, and energy technology. Equipped with two logically separated IP address interfaces each with 2 integrated Fast Ethernet ports. Configurable assignment of the Ethernet ports for the use of the spanning-tree protocol, daisy chain and redundant ring structures for maximum availability. Four LAN, two USB, and two RS-485 interfaces are integrated. The data point connections can be extended with up to 63 Inline I/O modules: digital and analog, function terminals for DALI, pulse counting, MBUS or serial interfaces.

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com