

EEM-RS485-MA400


Order No.: 2901365



<http://eshop.phoenixcontact.ae/phoenix/treeViewClick.do?UID=2901365>

RS-485 JBUS/MODBUS communication module for EEM-MA400

Commercial data

EAN	
Pack	1 pcs.
Customs tariff	90303100
Gross weight in pieces	132.20 g

Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation at <http://www.download.phoenixcontact.com>. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Interfaces

Name	Modbus RTU/JBUS
Interface	RS-485
Connection method	COMBICON plug-in screw terminal block
	2, 3-wire
Transmission length	≤ 1200 m
Termination resistor	120 Ω (switchable via DIP switches)
Operating mode	semiduplex
Serial transmission speed	2,4 ... 38.4 kbps

General data

Width	22.5 mm
Height	65 mm

Depth	48 mm
Supply voltage	9 V (via EEM-MA400)
Degree of protection	IP20
Color	black
Conformance	CE-compliant
Rated insulation voltage	300 V AC (EN 61010-1)
Surge voltage category	III
Test voltage	3.5 kV AC (50 Hz, 1 min.) 2.2 kV AC (50 Hz, 1 min.)
Ambient temperature (operation)	-10 °C ... 55 °C (14 °F to 131 °F)
Ambient temperature (storage/transport)	-20 °C ... 85 °C (-4 °F ... 185 °F)
Max. permissible relative humidity (operation)	≤ 95 %
Salt spray	≤ 2.5 %

Connection data

Conductor cross section stranded min.	0.5 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section solid min.	0.5 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	20
Conductor cross section AWG/kcmil max	14
Connection method	COMBICON plug-in screw terminal block
Stripping length	6 mm
Tightening torque	0.4 Nm

Certificates



Certification cULus Listed

Certifications applied for:

Certification Ex:

Address

PHOENIX CONTACT Middle East FZ LLC
Office 301, Third Floor, Block 10, Dubai International
Academic City (DIAC)
Dubai, United Arab Emirates
Phone +971 4 437 0324
Fax +971 4 437 0323
<http://www.phoenixcontact.com>

PHOENIX CONTACT Middle East FZ LLC
Technical modifications reserved;