

100 ASTM



Friction Tape

Technical Data Sheet October 2017

Description and Features

A high quality cotton fabric coated on both sides with a black rubber adhesive compound, which provides good adhesion to all types of surfaces. A 0,38mm general-purpose tape that provides excellent protection against abrasion. ASTM-D-4514, Comm. Spec. 6747, HHT 101A.

- Adhesive compound on both sides
- · Adheres to metal, cable and wire
- · Good mechanical strength
- Meets Comm. Spec. 6747, HHT 101A

Materials	Backing Adhesive Cotton Rubber fabric		Color Black	Standard Sizes Width x Length 19 mm x 18 m (0.75 in. x 59 ft.) 51 mm x 18 m (2 in. x 59 ft.) Other sizes available upon request	
Technical Properties	Characteris	stic		Typical Value	Test Method
	Thickness (mm)			0.38	ASTM D 4514
	Tensile strength (N/cm) Adhesion			70	ASTM D 4514
	Standard (mm/min)			380	ASTM D 4514
	Oven test (mm/min)			380	ASTM D 4514
	Copper corrosion (visual)			Pass	ASTM D 69
	Dielectric breakdown (V)			1200	ASTM D 69
Recommended Uses	For providing mechanical protection against abrasion and penetration of cable, splices and wire. It is a temporary binding and harnessing tape and has a multitude of miscellaneous general-purpose uses. Apply over tool handles for a non-slip surface				
Storage	In original packaging, placed in horizontal position under cover and temperature between 5°C and 35 °C.				
Shelf Life	24 months from date of manufacture.				

Information provided is for reference only. Data in table represent average test results and are not to be used for specification purposes. The product user should make his/her own tests to determine the product's suitability for the intended use

LIMITED WARRANTY: Plymouth warrants that its Product will substantially conform to that products written specifications for a period of one (1) year from the date of shipment, (Unless provided otherwise). Plymouth makes no warranty to the distributor, its customers, or the product's end user for the products merchantability and/or suitability for his/its intended use or purpose, and buyer shall assume all risks associated therewith. Provided that the product is proved to be defective within the terms described above, and provided buyer shall have first compiled with all return policies of Plymouth, PLYMOUTH'S SOLE OBLIGATION AND BUYER'S EXCLUSIVE REMEDY UNDER THIS PRODUCT WARRANTY SHALL BE TO REPLACE SUCH QUANTITY OF THE PRODUCT AS IS PROVED TO BE DEFECTIVE WITHIN THE TIME PERIOD SPECIFIED ABOVE. EXCEPT AS EXPRESSLY SET FORTH HEREIN, PLYMOUTH MAKES NO OTHER ARRANTIES, EXPRESS OR IMPLIED. In no event shall Plymouth be liable for collateral, consequential, indirect or incidental damages arising out of, or connected in any way with the supply of products. (Rev. 1/2017-2019)