

## **Specification Sheet**

Part Number: 183-28080


Narrow slots suitable for small-diameter wires.

Fingers can be removed with no sharp edges at pre-notched snap-off

points.

Duct covers hold securely even in a vertical position and under vibration.

Base perforation according to DIN EN 50085.



Article Number 183-28080

Type HTWD-HF-80X80

Color Gray (GY)

Quantity Per box

Product Description HelaDuct HTWD-HF wiring duct is used to route and protect wires in

control panels and switching systems where there are high demands on personal or material safety in case of fire, such as in public transport, tunnels, data processing centers or public buildings. Snap-on covers are included with corresponding duct sizes to ensure complete wire

protection.

Short Description Halogen Free Slotted Wiring Duct & Cover, w/o Adhesive, 80mm x

80mm, PC/ABS, Gray, 12 m/Box

Global Part Name

HTWD-HF-80X80-PC/ABS-GY

Length L (Imperial)

6.56

Length L (Metric)

2.0

**Fixation Method** 

**Screw Mounting** 

Width W (Imperial)

3.15

Width W (Metric)

80.0

Height H (Imperial)

3.15

Height H (Metric)

80.0

Material

Acrylonitrile Butadiene Styrene alloyed with Polycarbonate (PC/ABS)

**Material Shortcut** 

PC/ABS

Flammability

UL 94 V-0

Halogen Free

Yes

UV Resistant (Yes/No)

No

**Operating Temperature** 

-13°F to +194°F (-25°C to +90°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant	Yes
Certification/Specification	UL   ANSI/UL 1565 UL   ANSI/UL 62275 UL   csa-C22.2 no. 18.5 UL   csa-C22.2 no. 62275 EN [45545-2]
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	12
Package Quantity (Metric)	12.0
Customs Number	3925900000

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

 $\hbox{@\,}2023$  HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions