



- CONNECTOR DIMENSIONS ARE PER ARINC 600 SPECIFICATION
- DUST COVER INSTALLED FOR SHIPPING.
- KEYING SHOWN IN POSITION "01" FOR REFERENCE ONLY. SEE TABLE FOR KEYING POSITION. FOR POSITION "00" KEYING SHIPPED UNASSEMBLED.
- CONTACTS PACKAGED SEPARATELY AND SHIPPED WITH CONNECTOR.

COMPONENT	MATERIAL	FINISH
SHELL	DIE CAST ALUMINUM PER ASTM-B-85	ELECTROLESS NICKEL PER MIL-C-26074
INSERT RETENTION PLATES	ALUMINUM ALLOY PER ASTM-B-209	ELECTROLESS NICKEL PER MIL-C-26074
SCREWS AND LOCKWASHERS	STEEL OR STAINLESS STEEL	CHROMATE OVER ZINC OR PASSIVATED
POLARIZING KEYS	ZINC ALLOY PER ASTM-B-86	-
POLARIZING KEY RETAINING PLATE	ALUMINUM ALLOY PER ASTM-B-209	BLUE ANODIZED PER MIL-A-8625
INSERTS	THERMOSET OR THERMOPLASTIC PPS PER MIL-M-24519	-
DUST COVER	CONDUCTIVE THERMOPLASTIC	-

"00"	MODULE A 208264-2 (SZ 22 CRIMP SOCKET CONTACT; QTY=150)	1996952-1
	MODULE B 208265-3 (SZ 20 CRIMP PIN CONTACT; QTY=60)	
KEYING POSITION	CONTACTS INCLUDED AND NOT INSTALLED	PART NUMBER
	MODULE C 208265-3 (SZ 20 CRIMP PIN CONTACT; QTY=24) 208268-3 (SZ 16 CRIMP PIN CONTACT; QTY=10)	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIN: C.C.THOMAS 10-3-08
 CHK: K.THACKSTON 10-3-08
 APVD: K.THACKSTON 10-3-08

TOLERANCES UNLESS OTHERWISE SPECIFIED:
 0 PLC ± -
 1 PLC ± -
 2 PLC ± -
 3 PLC ± -
 4 PLC ± -
 ANGLES ± -

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION

APVD: K.THACKSTON 10-3-08

RCPT ASSY, SIZE 2, ARINC 600 (150/60/34), RR

SIZE: A1
 CAGE CODE: 00779
 DRAWING NO: 1996952

RESTRICTED TO: -

CUSTOMER DRAWING

SCALE: 3:2 SHEET: 1 OF 1 REV: A