



Key-operated switch IKON, 22 mm, round, metal, shiny, lock number 360012K1, with 2 keys, 2 switch positions O<I, momentary contact type, Actuating angle 45°, 10:30h/12h, key removal O, with laser labeling, inscription or symbol Customer-specific selection with SIRIUS ACT configurator (CIN)

|                                                    |                                                                                                                            |
|----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| product brand name                                 | SIRIUS ACT                                                                                                                 |
| product designation                                | Key-operated switches                                                                                                      |
| design of the product                              | Actuating/signaling element                                                                                                |
| product type designation                           | 3SU1                                                                                                                       |
| product line                                       | Metal, shiny, 22 mm                                                                                                        |
| manufacturer's article number of included key      | <a href="#">3SU1950-0FR80-0AA0</a>                                                                                         |
| <b>Actuator</b>                                    |                                                                                                                            |
| principle of operation of the actuating element    | momentary contact, 45° (10:30 h/12 h), return from center to left                                                          |
| product extension optional light source            | No                                                                                                                         |
| color                                              |                                                                                                                            |
| • of the actuating element                         | silver                                                                                                                     |
| material of the actuating element                  | metal                                                                                                                      |
| shape of the actuating element                     | Key                                                                                                                        |
| outer diameter of the actuating element            | 29.5 mm                                                                                                                    |
| marking of the actuating element                   | Any inscription, text or symbol, can only be ordered via SIRIUS ACT configurator/Configuration Identification Number (CIN) |
| number of switching positions                      | 2                                                                                                                          |
| switch position for key distraction                | O                                                                                                                          |
| actuating angle                                    |                                                                                                                            |
| • clockwise                                        | 45°                                                                                                                        |
| lock make                                          | ICON                                                                                                                       |
| key number                                         | 360012K1                                                                                                                   |
| <b>Front ring</b>                                  |                                                                                                                            |
| product component front ring                       | Yes                                                                                                                        |
| design of the front ring                           | Standard                                                                                                                   |
| material of the front ring                         | Metal, high gloss                                                                                                          |
| color of the front ring                            | silver                                                                                                                     |
| <b>General technical data</b>                      |                                                                                                                            |
| protection class IP                                | IP66, IP67, IP69(IP69K)                                                                                                    |
| • of the terminal                                  | IP20                                                                                                                       |
| degree of protection NEMA rating                   | 1, 2, 3, 3R, 4, 4X, 12, 13                                                                                                 |
| shock resistance                                   |                                                                                                                            |
| • according to IEC 60068-2-27                      | sinusoidal half-wave 15g / 11 ms                                                                                           |
| vibration resistance                               |                                                                                                                            |
| • according to IEC 60068-2-6                       | 10 ... 500 Hz: 5g                                                                                                          |
| operating frequency maximum                        | 1 800 1/h                                                                                                                  |
| mechanical service life (switching cycles) typical | 300 000                                                                                                                    |
| reference code according to IEC 81346-2            | S                                                                                                                          |
| Substance Prohibitance (Date)                      | 10/01/2014                                                                                                                 |

| Ambient conditions                                             |                                                                    |
|----------------------------------------------------------------|--------------------------------------------------------------------|
| <b>ambient temperature</b>                                     |                                                                    |
| • during operation                                             | -25 ... +70 °C                                                     |
| • during storage                                               | -40 ... +80 °C                                                     |
| environmental category during operation according to IEC 60721 | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%) |
| Installation/ mounting/ dimensions                             |                                                                    |
| <b>height</b>                                                  | 29.5 mm                                                            |
| <b>width</b>                                                   | 29.5 mm                                                            |
| <b>shape of the installation opening</b>                       | round                                                              |
| <b>mounting diameter</b>                                       | 22.3 mm                                                            |
| <b>positive tolerance of installation diameter</b>             | 0.4 mm                                                             |
| <b>mounting height</b>                                         | 56.2 mm                                                            |
| <b>installation width</b>                                      | 29.5 mm                                                            |
| <b>installation depth</b>                                      | 25.4 mm                                                            |
| Certificates/ approvals                                        |                                                                    |
| Further information                                            |                                                                    |

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1050-5XC01-0AA0-Z Y19>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1050-5XC01-0AA0-Z Y19>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1050-5XC01-0AA0-Z Y19>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1050-5XC01-0AA0-Z Y19&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1050-5XC01-0AA0-Z Y19&lang=en)

last modified:

1/26/2022 