

https://www.phoenixcontact.com/us/products/1290807



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



IP66 Touch panel with 18.5-inch widescreen (16:9) HD, PCAP display, Software: Qt Browser

## Your advantages

- Easy startup just enter the IP and URL
- · Flexible, thanks to open web standard and free choice of web server and visualization software
- No security updates are required for JAVA or Flash plug-ins thanks to HTML5
- · Ideal for use with PLCnext Engineer or CODESYS
- Embedded Linux operating system
- Visualization of self-programmed JavaScript applications possible

#### Commercial data

Item number	1290807
Packing unit	1 pc
Sales key	DR17
Product key	DRCADF
GTIN	4063151523046
Weight per piece (including packing)	2,260 g
Weight per piece (excluding packing)	2,100 g
Country of origin	TW



https://www.phoenixcontact.com/us/products/1290807



## Technical data

### Product properties

Product type	Operator panel
Computer data	
Processor	Arm <sup>®</sup> Cortex <sup>®</sup> -A53, 1.6 GHz
Operating system	Yocto/Linux
Data storage system	Flash eMMC, 8 GB
Slots	1x microSD
Display	
Display type	46.9 cm/18.5" TFT
Screen resolution	1920 x 1080 Pixel(s) (Full HD)
Touch technology	projective-capacitive (PCAP)
Display lighting type	LED
Brightness	350 cd/m², typical (adjustable)
MTBF	50000 h
Color spectrum	16.7 million colors
Reading angle left	89 °
Reading angle right	89 °
Reading angle top	89 °
Reading angle bottom	89 °

#### Software

User software	QT browser
System requirements	
Runtime system	Qt Browser

### Interfaces

Interfaces	2x USB Host 2.0, 1x USB Type C 3.0
	1x COM (RS-232/422/485)
Optional interfaces	Without optional interface
Network	1x Ethernet (10/100/1000 Mbps), RJ45
Bus system	without

### System properties

User software	QT browser
System requirements	
Runtime system	Qt Browser

## Electrical properties

Supply



https://www.phoenixcontact.com/us/products/1290807



Supply voltage	24 V DC
Supply voltage range	18 V 32 V
Power supply unit	24 V DC ±20 %
Real-time clock	
Realtime clock	Integrated (battery backup)
Mounting	
Mounting type	Front mounting
Material specifications	
Material front plate	Aluminum (natural anodized)
Housing material	Aluminum cast alloy, powder-coated
Connection data	
Connection method	Screw connection
Conductor cross section, rigid	0.2 mm <sup>2</sup> 2.5 mm <sup>2</sup>
Conductor cross section, flexible	0.2 mm <sup>2</sup> 2.5 mm <sup>2</sup>
Conductor cross section AWG	24 12
Stripping length	7 mm

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP66 (front), IP20 (back)
Ambient temperature (operation)	0 °C 50 °C
Ambient temperature (storage/transport)	-20 °C 60 °C
Permissible humidity (operation)	10 % 95 % (non-condensing)
Permissible humidity (storage/transport)	10 % 95 % (non-condensing)
Vibration (operation)	1g

#### Dimensions

### External dimensions

Width / Height / Depth	465 mm / 310 mm / 51 mm (Dimensions of the front plate)
Installation dimensions	
Width / Height / Installation depth	455 mm / 300 mm / (Installation cutout)



https://www.phoenixcontact.com/us/products/1290807



## **Approvals**

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1290807



**IECEE CB Scheme** 

Approval ID: US-39088-UL



EAC

Approval ID: RU C-DE.A\*08.B01708



**UL Listed** 

Approval ID: FILE E 238705



cUL Listed

Approval ID: FILE E 238705

**cULus Listed** 



https://www.phoenixcontact.com/us/products/1290807



## Classifications

UNSPSC 21.0

#### **ECLASS**

ECLASS-11.0	27330201
ECLASS-12.0	27330201
ECLASS-13.0	27330201
ETIM	
ETIM 8.0	EC001412

43211900



https://www.phoenixcontact.com/us/products/1290807



## Environmental product compliance

REACh SVHC Lead 7439-92-1

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com