

# FUSES

## GLASS BODY

### 8AG Fast-Acting Instrument Type

QPL<sup>®</sup>

#### ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Opening Time
100%	4 hours, <b>Minimum</b>
200%	5 seconds, <b>Maximum</b>

FUSES TO MIL SPEC:<sup>®</sup> See F01A type in Military Section.



FUSE DIMENSIONS:  
Diameter: 1/4"  
Length: 1"

#### ORDERING INFORMATION:

Catalog Number	Ampere Rating	Voltage Rating
361.002	1/500	250
361.005	1/200	250
361.010	1/100	250
361.015	1/64	250
361.031	1/32	250
361.062	1/16	250
361.100	1/10	250
361.125	1/8	250
361.187	3/16	250
361.200	3/10	250
361.250	1/4	250
361.375	3/8	250
361.400	1/2	250
361.500	3/4	250
361.600	1	250
361.750	1 1/2	250
361.001	2	250
361.01.5	3	125
361.002	4	125
361.003	5	125
361.004		
361.005		

### 8AG Fast-Acting Type

UL<sup>®</sup> CS<sup>®</sup>

#### ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Opening Time
110%	4 hours, <b>Minimum</b>
135%	1 hour, <b>Maximum</b>
200%	10 seconds, <b>Maximum</b>

APPROVALS:<sup>®</sup> Listed by Underwriters Laboratories through 6 amperes. Certified by CSA from 1/4 through 5 amperes.



FUSE DIMENSIONS:  
Diameter: 1/4"  
Length: 1"

#### ORDERING INFORMATION:

Catalog Number	Ampere Rating	Voltage Rating
362.125	1/8	250
362.250	1/4	250
362.375	3/8	250
362.500	1/2	250
362.750	3/4	250
362.001	1	250
362.1.25	1 1/4	250
362.01.5	1 1/2	250
362.002	2	250
362.02.5	2 1/2	125
362.003	3	125
362.004	4	125
362.005	5	125
362.006	6	125
362.007	7	125
362.008	8	32
362.010	10	32
362.012	12	32
362.015	15	32
362.020	20	32
362.025	25	32
362.030	30	32