

Part Name	ZTP-148SRC1	Part No.	IRF038M01-00A0	Rev.	0.0
-----------	-------------	----------	----------------	------	-----

## SPECIFICATION of THERMOPILE IR SENSOR

**Product Name: ZTP-148SRC1**



- 
- The information and design authority contained in this document is proprietary to Amphenol Advance Sensors and could be shared with any customers to promote.
- The information and design authority contained in this document is proprietary to Customer and shall not be disclosed in whole or in part in any form or for any reason.  
You are required to contact with Amphenol Advance Sensors product management for more information or any help
- The information and design authority contained in this document is generated by Amphenol Advance Sensors & Customer and shall not be disclosed in whole or in part in any form or for any reason.  
You are required to contact with Amphenol Advanced Sensors product management for more information or any help.

Part Name	ZTP-148SRC1	Part No.	IRF038M01-00A0	Rev.	0.0
-----------	-------------	----------	----------------	------	-----

## 1. Feature of ZTP-148SRC1

### 1.1 Thermopile Chip

Parameter	LIMITS			UNIT	CONDITION
	MIN	TYP	MAX		
CHIP SIZE		1.8 X 1.8		mm <sup>2</sup>	
DIAPHRAGM SIZE		1.0 X 1.0			
ACTIVE AREA		0.7 X 0.7		mm <sup>2</sup>	Absorber area
INTERNAL RESISTANCE	60	85	110	k $\Omega$	@25°C
RESISTANCE T.C			0.12	%/°C	
RESPONSIVITY		54		V/W	500K, 1Hz,
RESPONSIVITY T.C		-0.07		%/°C	
NOISE VOLTAGE		37		nV/Hz <sup>1/2</sup>	R.M.S, 25°C
NEP		0.69		nW/Hz <sup>1/2</sup>	
DETECTIVITY		1.02		cmHz <sup>1/2</sup> /W	
TIME CONSTANT		32		ms	

### 1.2 Thermistor

- NTC Thermistor for Temperature Compensation

Parameter	LIMITS			UNIT	CONDITION
	Min	Typ	Max		
RESISTANCE		100		k $\Omega$	Tolerance.: $\pm$ 3% @ 25°C
Beta – Value		3950		K	Tolerance.: $\pm$ 1% @ 25°C/50°C


### 1.3 Absolute maximum ratings

- Operating Temperature : -20°C ~ 100°C
- Storage Temperature : -40°C ~ 120°C

Part Name	ZTP-148SRC1	Part No.	IRF038M01-00A0	Rev.	0.0
-----------	-------------	----------	----------------	------	-----


## 2. Typical Characteristic data of ZTP-148SRC1

### 2.1 Sensitivity



### 2.2 Field of View

Parameter	LIMITS			Units	Condition
	Min	Typ	Max		
Field of View		85		Degree	50% of Maximum Output




Part Name	ZTP-148SRC1	Part No.	IRF038M01-00A0	Rev.	0.0
-----------	-------------	----------	----------------	------	-----

### 2.3 Thermistor Resistance table

Temperature (°C)	Minimum resistance(kΩ)	Typical resistance(kΩ)	Maximum resistance(kΩ)
-20	925.2	975.8	1028.2
-15	696.2	732.2	769.3
-10	528.9	554.7	581.2
-5	405.5	424.1	443.2
0	313.5	327.0	340.8
5	244.3	254.2	264.3
10	191.9	199.2	206.6
15	151.8	157.2	162.7
20	121.0	125.0	129.0
25	97.0	100.0	103.0
30	77.9	80.5	83.1
35	63.0	65.2	67.5
40	51.2	53.2	55.1
45	41.9	43.6	45.2
50	34.5	35.9	37.3
55	28.5	29.7	31.0
60	23.6	24.7	25.8
65	19.7	20.7	21.6
70	16.5	17.3	18.2
75	13.9	14.6	15.4
80	11.8	12.4	13.0
85	10.0	10.5	11.1
90	8.5	9.0	9.5
95	7.3	7.7	8.1
100	6.2	6.6	7.0

### 2.4 Transmission data of Filter



Part Name	ZTP-148SRC1	Part No.	IRF038M01-00A0	Rev.	0.0
-----------	-------------	----------	----------------	------	-----

### 3. Outline of Sensor package and pin arrangement [Unit : mm]

