5-1534798-9 ACTIVE

AMP DUOPLUG

TE Internal #: 5-1534798-9

Standard Edge Connectors, Wire-to-Board, 9 Position, .098 in [2.5 mm] Centerline, Insulation Displacement (IDC), 1 Row, Natural, PA 6 GF

View on TE.com >



Connectors > PCB Connectors > Card Edge Connectors > Standard Edge Connectors











Connector System: Wire-to-Board

Number of Positions: 9

Centerline (Pitch): 2.5 mm [.098 in]

Termination Method to Wire & Cable: Insulation Displacement (IDC)

Number of Rows: 1

Features

Product Type Features

| Connector System | Wire-to-Board |
|-----------------------------------|-----------------------|
| Connector & Housing Type | Receptacle |
| Connector & Contact Terminates To | Printed Circuit Board |
| Configuration Features | |
| Card Entry Style | Side |

| Comiguration reactives | |
|-----------------------------------|--------------------|
| Card Entry Style | Side |
| Compatible With Wire & Cable Type | Discrete Wire |
| Number of Positions | 9 |
| Number of Rows | 1 |
| Connector Contact Load Condition | Selectively Loaded |
| PCB Mount Orientation | Right Angle |
| | |

Electrical Characteristics

| Operating Voltage | 50 VAC, 250 VAC |
|-------------------|-----------------|
| | , |

Body Features

| Primary Product Color | Natural | |
|-----------------------|---------|--|



| Contact Features | |
|--|-------------------------------|
| Contact Retention Within Housing | With |
| Contact Type | Socket |
| Contact Mating Area Plating Material Thickness | 3 – 6 µm |
| Contact Mating Area Plating Material | Tin |
| PCB Contact Termination Area Plating Material | Tin |
| Contact Base Material | Copper Tin |
| Contact Current Rating (Max) | 2 A |
| Termination Features | |
| Termination Method to Wire & Cable | Insulation Displacement (IDC) |
| Mechanical Attachment | |
| Mating Alignment Type | Keyed |
| Mating Retention | Without |
| Mating Alignment | With |
| Contact Retention Type Within Housing | Locking Lance |
| PCB Mount Retention | Without |
| Connector Mounting Type | Cable Mount (Free-Hanging) |
| Housing Features | |
| Housing Entry Configuration | Both Ends Open |
| Centerline (Pitch) | 2.5 mm[.098 in] |
| Housing Material | PA 6 GF |
| Dimensions | |
| Connector Height | 7.3 mm[.287 in] |
| PCB Thickness (Recommended) | 1.5 mm[.059 in] |
| Compatible Insulation Diameter Range | 1.2 – 1.6 mm[.047 – .063 in] |
| Wire Size | .22 – .35 mm² |
| Usage Conditions | |
| Operating Temperature Range | -40 - 110 °C[-40 - 230 °F] |
| Operation/Application | |
| Circuit Application | Signal |
| Packaging Features | |
| | |



| Packaging Quantity | 6160 |
|--------------------|------|
| Packaging Method | Box |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|--|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUL 2021 (219) Does not contain REACH SVHC |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Not applicable for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts









Customers Also Bought





TE Part #3-1534796-0
AMP DUOPLUG MK2 CONNECTOR
10P




TE Part #4-1534797-2 DUOPLUG MARK II CONNECTOR



TE Part #1394918-6
DUOPLG5.0 BU-STE 6P




TE Part #1534415-8
DUOPL POW FEM CON8P



TE Part #1740533-5

AMP DUOPLUG POW CONN. 5POS

W.PCB LOCKING



TE Part #1-1355181-8
DUOPLUG2,5GEH 8P 6X



TE Part #3-1534797-3
AMP DUOPLUG MK2 CONNECTOR
13P



TE Part #3-1534797-4
AMP DUOPLUG MK2 CONNECTOR
14P



Documents

CAD Files

Customer View Model

ENG_CVM_CVM_5-1534798-9_A.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5-1534798-9_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-1534798-9_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

1654742_HOUSEHOLD_APPLIANCES_RAST2.5

English

Product Specifications

Standard Edge Connectors, Wire-to-Board, 9 Position, .098 in [2.5 mm] Centerline, Insulation Displacement (IDC), 1 Row, Natural, PA 6 GF



Application Specification

English

Product Environmental Compliance

TE Material Declaration

English

Agency Approvals

VDE Certificate

English

VDE Certificate

English