

External 192V Tower Battery Pack for select Tripp Lite UPS Systems (BP192V787C-16K)

MODEL NUMBER: BP192V787C-16K



Highlights

- Extends runtime of compatible Tripp Lite UPS Systems using 192VDC configuration
- Includes built in 7A charger
- Includes UPS connection cabling
- 10 year design life
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Description

Tripp Lite's BP192V787C-16K External Battery Pack with built-in 7A charger offers extended battery runtime when used in conjunction with compatible Tripp Lite UPS systems. Includes heavy gauge cabling to connect to host UPS. Multiple BP192V787C-16K batteries can be daisy-chained for longer runtime configurations with appropriate contractor-supplied battery pack interconnection cabling (see manual). Internal battery charger is powered via hardwire connection to 120V 30A electrical service.

COMPATIBLE UPS SYSTEMS: SU16000RT4U, SU16000RT4UHW and other Tripp Lite UPS systems specifying the use of this battery pack

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- 10 year design life
- Multiple battery packs can be daisy-chained through each other to the UPS for even longer extended run operation
- Cabling to connect one BP192V787C-16K to the host UPS is included - cabling for additional battery packs is contractor supplied
- Includes built-in 7A charger powered via hardwire 120VAC 30A input connection

Specifications

| OVERVIEW | |
|--------------------------------|---|
| UPC Code | 037332147615 |
| BATTERY | |
| Expandable Runtime | Yes |
| Expandable Runtime Description | Multiple battery packs can be daisy-chained to the UPS for extended runtime. Configuration specific cabling for multi-battery pack configurations is contractor provided. |

| | |
|-------------------------------------|--|
| DC System Voltage (VDC) | 192 |
| UPS Connection | Included cabling enables connection between unique UPS connector and hardwire DC terminals in battery pack. Cabling to connect multiple external battery packs is contractor provided. |
| PHYSICAL | |
| Material of Construction | Steel |
| External Battery Pack Form Factor | Tower |
| Shipping Dimensions (hwd / in.) | 0.00 x 0.00 x 0.00 |
| Shipping Dimensions (hwd / cm) | 0.00 x 0.00 x 0.00 |
| Shipping Weight (lbs.) | 1628.00 |
| Shipping Weight (kg) | 738.45 |
| Unit Dimensions (hwd / in.) | 60.000 x 32.000 x 30.000 |
| Unit Dimensions (hwd / cm) | 152.4 x 82.3 x 73.2 |
| Unit Weight (lbs.) | 1628 |
| Unit Weight (kg) | 738.45 |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | 1-year limited warranty |