

FMS7G15US60S

Compact & Complex Module

Features


- Short Circuit Rated $10\mu\text{s}$ @ $T_C = 100^\circ\text{C}$, $V_{GE} = 15\text{V}$
- High Speed Switching
- Low Saturation Voltage : $V_{CE(sat)} = 2.1\text{V}$ @ $I_C = 15\text{A}$
- High Input Impedance
- Built-in Brake & 1 Phase Rectifier Circuit
- Fast & Soft Anti-Parallel FWD
- Built-in NTC Thermistor

Applications


- AC & DC Motor Controls
- General Purpose Inverters
- Robotics
- Servo Controls

Description

Fairchild IGBT Power Module provides low conduction and switching losses as well as short circuit ruggedness. It's designed for the applications such as motor control and general inverters where short-circuit ruggedness is required.



Package Code : 25PM-AA



Internal Circuit Diagram

Absolute Maximum Ratings T_C = 25°C unless otherwise noted

| | Symbol | Description | FMS7G15US60S | Units |
|------------------|--------------------------|---|--------------|------------------|
| Inverter & Brake | V _{CES} | Collector-Emitter Voltage | 600 | V |
| | V _{GES} | Gate-Emitter Voltage | ± 20 | V |
| | I _C | Collector Current @ T _C = 80°C | 15 | A |
| | I _{CM(1)} | Pulsed Collector Current | 30 | A |
| | I _F | Diode Continuous Forward Current @ T _C = 80°C | 15 | A |
| | I _{FM} | Diode Maximum Forward Current | 30 | A |
| | P _D | Maximum Power Dissipation @ T _C = 25°C | 73 | W |
| | T _{SC} | Short Circuit Withstand Time @ T _C = 100°C | 10 | μs |
| Converter | V _{RRM} | Repetitive Peak Reverse Voltage | 1600 | V |
| | I _O | Average Output Rectified Current | 20 | A |
| | I _{FSM} | Surge Forward Current @ 1Cycle at 60Hz, Peak value Non-Repetitive | 200 | A |
| | i ² t | Energy pulse @ 1Cycle at 60Hz | 164 | A ² s |
| Common | T _J | Operating Junction Temperature | -40 to +150 | °C |
| | T _{STG} | Storage Temperature Range | -40 to +125 | °C |
| | V _{ISO} | Isolation Voltage @ AC 1minute | 2500 | V |
| Mounting Torque | Mounting part Screw @ M4 | 2.0 | N·m | |

Notes :

(1) Repetitive rating : Pulse width limited by max. junction temperature

Package Marking and Ordering Information

| Device Marking | Device | Package | Reel Size | Tape Width | Quantity |
|----------------|--------------|---------|-----------|------------|----------|
| FMS7G15US60S | FMS7G15US60S | 25PM-AA | -- | -- | -- |

(2) TMC2 Reliability test was done under -45°C ~ 125°C

Electrical Characteristics of IGBT @ Inverter $T_C = 25^\circ\text{C}$ unless otherwise noted

| Symbol | Parameter | Test Conditions | Min. | Typ. | Max. | Units |
|--------------------------------------|---|---|------|------|-----------|---------------------|
| Off Characteristics | | | | | | |
| BV_{CES} | Collector-Emitter Breakdown Voltage | $V_{GE} = 0V, I_C = 250\mu A$ | 600 | -- | -- | V |
| $\frac{\Delta BV_{CES}}{\Delta T_J}$ | Temperature Coeff. of Breakdown Voltage | $V_{GE} = 0V, I_C = 1mA$ | -- | 0.6 | -- | V/ $^\circ\text{C}$ |
| I_{CES} | Collector Cut-Off Current | $V_{CE} = V_{CES}, V_{GE} = 0V$ | -- | -- | 250 | μA |
| I_{GES} | Gate - Emitter Leakage Current | $V_{GE} = V_{GES}, V_{CE} = 0V$ | -- | -- | ± 100 | nA |
| On Characteristics | | | | | | |
| $V_{GE(th)}$ | Gate - Emitter Threshold Voltage | $I_C = 15mA, V_{CE} = V_{GE}$ | 5.0 | 6.5 | 8.5 | V |
| $V_{CE(sat)}$ | Collector to Emitter Saturation Voltage | $I_C = 15A, V_{GE} = 15V$ | -- | 2.1 | 2.7 | V |
| Dynamic Characteristics | | | | | | |
| C_{ies} | Input Capacitance | $V_{CE} = 30V, V_{GE} = 0V,$ $f = 1MHz$ | -- | 935 | -- | pF |
| C_{oes} | Output Capacitance | | -- | 81 | -- | pF |
| C_{res} | Reverse Transfer Capacitance | | -- | 18 | -- | pF |
| Switching Characteristics | | | | | | |
| $t_{d(on)}$ | Turn-On Delay Time | $V_{CC} = 300V, I_C = 15A,$ $R_G = 13\Omega, V_{GE} = 15V,$ Inductive Load, $T_C = 25^\circ\text{C}$ | -- | 65 | 130 | ns |
| t_r | Rise Time | | -- | 80 | 160 | ns |
| $t_{d(off)}$ | Turn-Off Delay Time | | -- | 80 | 160 | ns |
| t_f | Fall Time | | -- | 100 | 200 | ns |
| E_{on} | Turn-On Switching Loss | | -- | 0.3 | -- | mJ |
| E_{off} | Turn-Off Switching Loss | | -- | 0.3 | -- | mJ |
| $t_{d(on)}$ | Turn-On Delay Time | $V_{CC} = 300V, I_C = 15A,$ $R_G = 13\Omega, V_{GE} = 15V,$ Inductive Load, $T_C = 125^\circ\text{C}$ | -- | 70 | 140 | ns |
| t_r | Rise Time | | -- | 80 | 160 | ns |
| $t_{d(off)}$ | Turn-Off Delay Time | | -- | 90 | 180 | ns |
| t_f | Fall Time | | -- | 210 | 350 | ns |
| E_{on} | Turn-On Switching Loss | | -- | 0.33 | -- | mJ |
| E_{off} | Turn-Off Switching Loss | | -- | 0.5 | -- | mJ |
| T_{sc} | Short Circuit Withstand Time | $V_{CC} = 300V, V_{GE} = 15V$ @ $T_C = 100^\circ\text{C}$ | 10 | -- | -- | μs |
| Q_g | Total Gate Charge | $V_{CE} = 300V, I_C = 15A,$ $V_{GE} = 15V$ | -- | 45 | 60 | nC |
| Q_{ge} | Gate-Emitter Charge | | -- | 9 | 15 | nC |
| Q_{gc} | Gate-Collector Charge | | -- | 17 | 30 | nC |

Electrical Characteristics of DIODE @ Inverter $T_C = 25^\circ\text{C}$ unless otherwise noted

| Symbol | Parameter | Test Conditions | Min. | Typ. | Max. | Units | |
|----------|-------------------------------------|---|---------------------------|------|------|-------|----|
| V_{FM} | Diode Forward Voltage | $I_F = 15\text{A}$ | $T_C = 25^\circ\text{C}$ | -- | 1.9 | 2.8 | V |
| | | | $T_C = 100^\circ\text{C}$ | -- | 2.0 | -- | |
| t_{rr} | Diode Reverse Recovery Time | $I_F = 15\text{A}$ $di/dt = 30\text{ A}/\mu\text{s}$ | $T_C = 25^\circ\text{C}$ | -- | 75 | 150 | ns |
| | | | $T_C = 100^\circ\text{C}$ | -- | 100 | -- | |
| I_{rr} | Diode Peak Reverse Recovery Current | | $T_C = 25^\circ\text{C}$ | -- | 1.0 | 2.0 | A |
| | | | $T_C = 100^\circ\text{C}$ | -- | 1.3 | -- | |
| Q_{rr} | Diode Reverse Recovery Charge | | $T_C = 25^\circ\text{C}$ | -- | 40 | 150 | nC |
| | | | $T_C = 100^\circ\text{C}$ | -- | 65 | -- | |

Electrical Characteristics of DIODE @ Converter $T_C = 25^\circ\text{C}$ unless otherwise noted

| Symbol | Parameter | Test Conditions | Min. | Typ. | Max. | Units | |
|-----------|----------------------------|--------------------|---------------------------|------|------|-------|----|
| V_{FM} | Diode Forward Voltage | $I_F = 20\text{A}$ | $T_C = 25^\circ\text{C}$ | -- | 1.1 | 1.5 | V |
| | | | $T_C = 100^\circ\text{C}$ | -- | 1.0 | -- | |
| I_{RRM} | Repetitive Reverse Current | $V_R = V_{RRM}$ | $T_C = 25^\circ\text{C}$ | -- | -- | 8 | mA |
| | | | $T_C = 100^\circ\text{C}$ | -- | 5 | -- | |

Thermal Characteristics

| | Symbol | Parameter | Typ. | Max. | Units |
|-----------|-----------------|---|------|------|---------------------------|
| Inverter | $R_{\theta JC}$ | Junction-to-Case (IGBT Part, per 1/6 Module) | -- | 1.7 | $^\circ\text{C}/\text{W}$ |
| | $R_{\theta JC}$ | Junction-to-Case (DIODE Part, per 1/6 Module) | -- | 2.5 | $^\circ\text{C}/\text{W}$ |
| Brake | $R_{\theta JC}$ | Junction-to-Case (IGBT Part) | -- | 1.7 | $^\circ\text{C}/\text{W}$ |
| | $R_{\theta JC}$ | Junction-to-Case (DIODE Part) | -- | 2.5 | $^\circ\text{C}/\text{W}$ |
| Converter | $R_{\theta JC}$ | Junction-to-Case (DIODE Part, per 1/6 Module) | -- | 1.5 | $^\circ\text{C}/\text{W}$ |
| Weight | | Weight of Module | 60 | -- | g |

NTC Thermistor Characteristics

| | Symbol | Parameter | Tol. | Typ. | Units |
|------------|-----------|---|---------|------|------------------|
| Thermistor | R25 | Rated Resistance @ $T_c = 25^\circ\text{C}$ | +/- 5 % | 4.7 | $\text{K}\Omega$ |
| | B(25/100) | B - Value | +/- 3 % | 3530 | |

Typical Performance Characteristics

Figure 1. Typical Output Characteristics




Figure 2. Typical Saturation Voltage Characteristics




Figure 3. Saturation Voltage vs. Case Temperature at Variant Current Level




Figure 4. Transient Thermal Impedance




Figure 5. Saturation Voltage vs. V_GE





Figure 6. Saturation Voltage vs. V_GE



Typical Performance Characteristics (Continued)

Figure 7. Capacitance Characteristics




Figure 8. Turn-On Characteristics vs. Gate Resistance




Figure 9. Turn-Off Characteristics vs. Gate Resistance




Figure 10. Switching Loss vs. Gate Resistance




Figure 11. Turn-On Characteristics vs. Collector Current





Figure 12. Turn-Off Characteristics vs. Collector Current



Typical Performance Characteristics (Continued)

Figure 13. Switching Loss vs. Collector Current




Figure 14. Gate Charge Characteristics




Figure 15. SOA Characteristics




Figure 16. RBSOA Characteristics




Figure 17. Forward Characteristics





Figure 18. Reverse Recovery Characteristics



Typical Performance Characteristics (Continued)

Figure 19. Rectifier (Converter) Characteristics




Figure 20. Rectifier (Converter) Characteristics






Figure 21. NTC Characteristics



Mechanical Dimensions

25PM-AA



- Pin Coordinate

| Pin #No | Coordinate | |
|---------|------------|------|
| | x | y |
| 1 | 0.0 | 0.0 |
| 2 | -3.0 | 0.0 |
| 3 | -6.0 | 0.0 |
| 4 | -13.0 | 0.0 |
| 5 | -18.0 | 0.0 |
| 6 | -25.0 | 0.0 |
| 7 | -29.0 | 0.0 |
| 8 | -32.0 | 0.0 |
| 9 | -35.0 | 0.0 |
| 10 | -38.0 | 0.0 |
| 11 | -46.5 | 0.0 |
| 12 | -49.5 | 0.0 |
| 13 | -49.5 | 11.5 |
| 14 | -49.5 | 20.0 |
| 15 | -49.5 | 28.0 |
| 16 | -32.0 | 28.0 |
| 17 | -29.0 | 28.0 |
| 18 | -23.0 | 28.0 |
| 19 | -20.0 | 28.0 |
| 20 | -14.0 | 28.0 |
| 21 | -11.0 | 28.0 |
| 22 | 3.5 | 28.0 |
| 23 | 3.5 | 20.0 |
| 24 | 3.5 | 11.5 |
| 25 | 3.5 | 5.5 |

* datum pin : #1

* Pin Tilt : ± 0.15

Dimensions in Millimeters

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

| | | | | |
|--------------------------------------|---------------------|---------------|---------------------|-----------------|
| ACEx™ | FAST® | ISOPLANAR™ | PowerSaver™ | SuperSOT™-8 |
| ActiveArray™ | FASTr™ | LittleFET™ | PowerTrench® | SyncFET™ |
| Bottomless™ | FPS™ | MICROCOUPLER™ | QFET® | TinyLogic® |
| Build it Now™ | FRFET™ | MicroFET™ | QS™ | TINYOPTO™ |
| CoolFET™ | GlobalOptoisolator™ | MicroPak™ | QT Optoelectronics™ | TruTranslation™ |
| CROSSVOLT™ | GTO™ | MICROWIRE™ | Quiet Series™ | UHC™ |
| DOME™ | HiSeC™ | MSX™ | RapidConfigure™ | UltraFET® |
| EcoSPARK™ | I ² C™ | MSXPro™ | RapidConnect™ | UniFET™ |
| E ² CMOS™ | i-Lo™ | OCX™ | μSerDes™ | VCX™ |
| EnSigna™ | ImpliedDisconnect™ | OCXPro™ | SILENT SWITCHER® | Wire™ |
| FACT™ | IntelliMAX™ | OPTOLOGIC® | SMART START™ | |
| FACT Quiet Series™ | | OPTOPLANAR™ | SPM™ | |
| Across the board. Around the world.™ | | PACMAN™ | Stealth™ | |
| The Power Franchise® | | POP™ | SuperFET™ | |
| Programmable Active Droop™ | | Power247™ | SuperSOT™-3 | |
| | | PowerEdge™ | SuperSOT™-6 | |

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

| Datasheet Identification | Product Status | Definition |
|--------------------------|------------------------|---|
| Advance Information | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice. |
| Preliminary | First Production | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| Obsolete | Not In Production | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only. |

Rev. I16