

used for:

2 x JACK SCREW



2 x KNURLED NUT




2 x COUNTERSUNK-HEAD SCREW



2 x PAN-HEAD SCREW



1 x CABLE STRAIN RELIEF



| No. of pos. | A | B | C | D | E | F | Part No. Bulk package | Part No. Single package |
|-------------|------|------|------|-------|------|------|-----------------------|-------------------------|
| 15 | 42.3 | 33.3 | 37.0 | 39.75 | 14.5 | 10.0 | 165X14169X | 165X14169XE |
| 25 | 56.0 | 47.0 | 37.0 | 39.75 | 14.5 | 10.5 | 165X14179X | 165X14179XE |
| 37 | 72.5 | 63.5 | 37.0 | 39.75 | 14.5 | 10.5 | 165X14189X | 165X14189XE |
| 50 | 67.0 | 61.1 | 49.1 | 51.40 | 19.8 | 14.0 | 165X14199X | 165X14199XE |

HOOD ASSEMBLY CONSISTS OF:

1. HOOD: ABS UL 94 V-0; GREY
2. JACK SCREW: BRASS; NICKEL PLATED
3. KNURLED NUT: BRASS; NICKEL PLATED
4. COUNTERSUNK-HEAD SCREW: STEEL; NICKEL PLATED
5. PAN-HEAD SCREW: STEEL; NICKEL PLATED
6. CABLE STRAIN RELIEF: STEEL; NICKEL PLATED

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.
 OWNERSHIP AND COPYRIGHT OF CONEC GmbH
 DO NOT ALTER CAD DRAWING BY HAND

| tolerance | | dim. in mm | |
|-----------|-------------|------------|------|
| 2011 | date | name | |
| drawn | 20.01. | Henneboel | |
| appd. | 20.01. | Fischer | |
| norm | | | |
| d-old | | | |
| a | Origin | | |
| rev. | description | date | name |



| | |
|-----------|---|
| scale: | 1:1 |
| material: | SEE NOTES |
| title: | PLASTIC HOOD 15pos. / 25pos. / 37pos. / 50pos. with straight cable exit and jack screws |
| dwg no: | 16K1A2762 |
| part no: | SEE TABLE |
| DIN-A | 4 |
| sh: | 1/1 |