



| PART NUMBER | DIMENSION "L" (MM) |
|-------------|--------------------|
| 203263-0106 | 26.00 |
| 203263-0116 | 20.00 |
| 203263-0126 | 14.00 |
| 203263-0136 | 31.75 |
| 203263-0146 | 29.50 |
| 203263-0156 | 16.00 |
| 203263-0176 | 37.20 |
| 203263-0186 | 31.00 |
| 203263-0196 | 26.75 |
| 203263-0206 | 16.80 |
| 203263-0226 | 21.50 |
| 203263-0246 | 36.00 |
| 203263-0256 | 48.00 |
| 203263-0266 | 27.70 |

NOTES :

- MATERIALS:
 - BASE METAL: HIGH CONDUCTIVE COPPER ALLOY
 - PLATING ON BODY: 3.18 MICRON MIN SILVER OVER 1.27 MICRON MIN NICKEL
- PRODUCT SPECIFICATION: 2043130006-PS
- APPLICATION SPECIFICATION: 2043130006-AS
- PACKAGING SPECIFICATION: 2032630006-PK
- SILVER COMPONENTS WILL BE SUPPLIED TARNISH FREE BUT MAY TARNISH OVER TIME
- MINIMUM RECOMMENED PCB THICKNESS 1.58MM

| | | | | | | | | | | | |
|---|--|---------------------|--|---|--|-------------------|--|---------------|--|---|--|
| THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | | | | | | | | | | |
| DIMENSION UNITS mm | | SCALE 5:1 | | CURRENT REV DESC: UPDATED THE DESCRIPTION | | | | | | molex | |
| GENERAL TOLERANCES (UNLESS SPECIFIED) | | | | EC NO: 726284 | | | | | | | |
| ANGULAR TOL $\pm 0.5^\circ$ | | | | 4 PLACES \pm | | DRWN: SOURAJ | | 2022/10/26 | | SENTRALITY 6.00MM MALE TERMINAL SURFACE MOUNT | |
| 4 PLACES \pm | | | | 3 PLACES \pm | | CHK'D: SUVARS | | 2022/10/27 | | | |
| 2 PLACES ± 0.15 | | | | 2 PLACES ± 0.15 | | APPR: GSHARMA | | 2022/10/28 | | PRODUCT CUSTOMER DRAWING | |
| 1 PLACE ± 0.25 | | | | 1 PLACE ± 0.25 | | INITIAL REVISION: | | DRWN: RLOW | | 2019/06/05 | |
| 0 PLACES \pm | | | | 0 PLACES \pm | | APPR: BPISZCZOR | | 2019/06/10 | | DOCUMENT NUMBER 2032630136-SD | |
| DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | | | | THIRD ANGLE PROJECTION | | DRAWING | | SERIES | | MATERIAL NUMBER | |
| | | | | | | D-SIZE | | 203263 | | CUSTOMER SEE TABLE | |
| | | | | | | | | | | GENERAL MARKET | |
| | | | | | | | | | | SHEET NUMBER 1 OF 1 | |