2085945-3 ACTIVE

QSFP/QSFP+

TE Internal #: 2085945-3

QSFP, QSFP+ & zQSPF+, Cage Assembly with Integrated

Connector, 2 x 1, Elastomeric Gasket, Included Lightpipe,

Standard, QSFP/QSFP+

View on TE.com >



Connectors > Pluggable IO Connectors & Cages > QSFP, QSFP+ & zQSPF+



Pluggable I/O Product Type: Cage Assembly with Integrated Connector

Port Matrix Configuration: 2x1

EMI Containment Feature Type: Elastomeric Gasket

Included Lightpipe: Yes
Enhancements: Standard

Features

Product Type Features

Form Factor	QSFP+
Cage Type	Stacked
Pluggable I/O Product Type	Cage Assembly with Integrated Connector
Connector System	Cable-to-Board
Sealable	Yes
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Port Matrix Configuration	2 x 1
Number of Ports	2
Lightpipe Configuration	All Four Left Indicator Up
Number of Rear EONs per Port Column	0
Number of Positions	76

Electrical Characteristics

Data Pata (May)	14 Gb/s
Data Rate (Max)	14 00/5

Contact Features

Contact Mating Area Plating Material Thickness	.76 μm[30 μin]
Contact Mating Area Plating Material	Gold



Contact Underplating Material	Tin
PCB Contact Termination Area Plating Material	Gold
Termination Features	
Termination Post & Tail Length	2.05 mm[.08 in]
Termination Method to Printed Circuit Board	Through Hole - Press-Fit
Mechanical Attachment	
Connector Mounting Type	Board Mount
Housing Features	
Cage Material	Nickel Silver
Centerline (Pitch)	.8 mm[.032 in]
Dimensions	
PCB Thickness (Recommended)	1.57 mm[.062 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Heat Sink Compatible	No
For Use With Pluggable I/O Products	QSFP Cable Assembly, QSFP MSA Compatible Transceiver
Pluggable I/O Applications	SFP+ Stacked Belly-to-Belly
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Box & Tray
Other	
EMI Containment Feature Type	Elastomeric Gasket
Included Lightpipe	Yes
Enhancements	Standard

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant	
------------------------------	-----------	--



EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





















KIT, EXTRACTION TOOL, QSFP+



TE Part # 2202165-4 QSFP TO QSFP, 26AWG, FDR, 4.0 **METER**



TE Part # 2202165-5 QSFP TO QSFP, 26AWG, FDR, 5.0 **METER**



TE Part # 2829040-4 QSFP IB EDR, 30AWG, 1.0M



Also in the Series | QSFP/QSFP+



Heat Sinks(1)



Pluggable I/O Cable Assemblies(23) QSFP, QSFP+ & zQSPF+(168)



Customers Also Bought













Documents

Product Drawings

QSFP+ Assy, 2x1, Gskt, 4LP-All, Sn EONs

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2085945-3_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2085945-3_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2085945-3_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English