

CUSTOMER PRINT


er: W8C80-6PG-P-5XX

PART NUMBE

DIMENSIONS IN BRACKETS [ ] ARE IN MILLIMETERS

**RoHS COMPLIANT** 

ASSEMBLY P/N	CONTACT QTY.		CABLE O.D. RANGE
	#16	#20	
W8C80-6PG-P-513	2	4	.1315 [3.3-3.8]
W8C80-6PG-P-516			.1618 [4.1-4.6]
W8C80-6PG-P-519			.1921 [4.8-5.3]
W8C80-6PG-P-522	2		.2225 [5.6-6.]
W8C80-6PG-P-526			.2527 [6.4-6.9]
W8C80-6PG-P-528			.26285 [6.6-7.2]



WIRING END

BACKSHELL MAT'L: UV PBT, BLACK

MA 07-15-20		RELEASED PER PDR 16014-10							
	PNK	01-18-18	PDR16014						
Ι.	INIT.	DATE	DESCRIPTION						
L INFORMATION ILLUSTRATED IS THE PROPERTY OF "CONXALL DRPORATION." UNAUTHORIZED		orig. drawn PNK		date: 01-18-18					
PLICATION OR DISTRIBUTION OF HIS DOCUMENT IS PROHIBITED.		CHECKED BY:			(2011) (2011)				
ALL UNITS ARE IN FEET.					601 E. WILDWOOD VILLA PARK, IL 60181				
NCHES, FRACTION OF INCHES AND DECIMALS. UNLESS OTHERWISE SPECIFIED		APPROVED BY:			TITLE: CABLE-TO-CABLE ASSEMBLY 2-16 + 4-20 PIN CONTACTS, CRIMP				
TOLERANCES: 3 PLACE DECIMALS ±.010 ANGLES ±1° FRACTIONS ±1/16		scale NTS	size B	sheet 1 OF 1	INSTA-CLICK™ MINI-CON-X POWER/SIGNA customer: STANDARD PRODUCT				
		FILE: DIRECTORY: W8C80-6PG-P-5XX SI W			PART NUMBER: W8C80-6PG-P-5XX	REV			