AMP-LATCH

TE Internal #: 746611-7

Ribbon Cable Connectors, Wire-to-Board, 8 Position, 2.54 mm [.1

in] Centerline, Vertical, Through Hole - Solder, 2 Row, Plug,


Standard Profile

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > FFC, FPC & Ribbon Connectors > Ribbon Cable Connectors











Connector System: Wire-to-Board

Number of Positions: 8

Centerline (Pitch): 2.54 mm [.1 in]
PCB Mount Retention: Without
PCB Mount Orientation: Vertical

Features

Product Type Features

| Ribbon Cable Connector Header Type | Pin Header |
|------------------------------------|-------------------------------------|
| Connector Product Type | Connector Assembly |
| Connector System | Wire-to-Board |
| Connector & Housing Type | Plug |
| Connector & Contact Terminates To | Printed Circuit Board, Wire & Cable |
| Configuration Features | |
| Number of Positions | 8 |
| PCB Mount Orientation | Vertical |
| Number of Rows | 2 |
| Electrical Characteristics | |
| Insulation Resistance | 5000 MΩ |
| | |

250 VAC

Operating Voltage

Daisy Chain Without



| Primary Product Color | Black |
|---|-------------------------------|
| Connector Profile | Standard |
| Contact Features | |
| PCB Contact Termination Area Plating Material Thickness | .762 μm[30 μin] |
| Contact Layout | Inline |
| Contact Type | Pin |
| Wire Contact Termination Area Plating Thickness | .127 μm[5 μin] |
| Wire Contact Termination Area Plating Material | Gold |
| Contact Mating Area Plating Material Thickness | .76 μm[29.92 μin] |
| PCB Contact Termination Area Plating Material | Gold |
| Contact Base Material | Phosphor Bronze |
| Contact Current Rating (Max) | 1 A |
| Termination Features | |
| Rectangular Termination Post & Tail Thickness | .32 mm[.013 in] |
| Rectangular Termination Post & Tail Width | .5 mm[.02 in] |
| Termination Post & Tail Length | 3.94 mm[.155 in] |
| Termination Method to Wire & Cable | Insulation Displacement (IDC) |
| Termination Method to Printed Circuit Board | Through Hole - Solder |
| Mechanical Attachment | |
| Mating Alignment | With |
| PCB Mount Alignment | Without |
| Panel Mount Feature | Without |
| PCB Mount Retention | Without |
| Mating Alignment Type | Polarization |
| Mating Retention | Without |
| Connector Mounting Type | Board Mount |
| Housing Features | |
| Housing Material | Thermoplastic |
| Centerline (Pitch) | 2.54 mm[.1 in] |
| Dimensions | |
| Connector Length | 12.4 mm[.488 in] |
| Connector Height | 6.43 mm[.253 in] |



| Wire Size .051 – .15 mm² PCB Thickness (Recommended) 3.18 mm[.125 in] Compatible Insulation Diameter Range .81 – 1.07 mm[.032 – .042 in] Row-to-Row Spacing 2 mm[.3 in] Usage Conditions Operating Temperature Range -65 – 105 °C[-85 – 221 °F] Operation/Application Solder Process Feature Solder Dipped Circuit Application Signal Industry Standards UI. Rating Recognized Agency/Standard CSA, UL Approved Standards UL Flammability Rating UL 94V-0 | Connector Width | 10.67 mm[.42 in] |
|--|--------------------------------------|-------------------------------|
| Compatible Insulation Diameter Range Row-to-Row Spacing 2 mm[.3 in] Usage Conditions Operating Temperature Range -65 - 105 °C[-85 - 221 °F] Operation/Application Solder Process Feature Circuit Application Industry Standards UL Rating Recognized Agency/Standard CSA, UL Approved Standards UL Flammability Rating UL Patv-0 UL 94V-0 | Wire Size | .051 – .15 mm² |
| Row-to-Row Spacing 2 mm[.3 in] Usage Conditions Operating Temperature Range -65 – 105 °C[-85 – 221 °F] Operation/Application Solder Process Feature Solder Dipped Circuit Application Signal Industry Standards UL Rating Recognized Agency/Standard CSA, UL Approved Standards UL Flammability Rating UL 94V-0 | PCB Thickness (Recommended) | 3.18 mm[.125 in] |
| Usage Conditions Operating Temperature Range -65 – 105 °C[-85 – 221 °F] Operation/Application Solder Process Feature Solder Dipped Circuit Application Signal Industry Standards UL Rating Recognized Agency/Standard CSA, UL Approved Standards UL Flammability Rating UL 94V-0 | Compatible Insulation Diameter Range | .81 – 1.07 mm[.032 – .042 in] |
| Operation/Application Solder Process Feature Circuit Application Signal Industry Standards UL Rating Agency/Standard Approved Standards UL Flammability Rating Operation/Application Solder Dipped Signal Signal Circuit Application Signal Recognized CSA, UL CSA, UL UL Flammability Rating UL 94V-0 | Row-to-Row Spacing | 2 mm[.3 in] |
| Operation/ApplicationSolder Process FeatureSolder DippedCircuit ApplicationSignalIndustry StandardsUL RatingRecognizedAgency/StandardCSA, ULApproved StandardsCSA LR7189, UL E28476UL Flammability RatingUL 94V-0 | Usage Conditions | |
| Solder Process Feature Circuit Application Industry Standards UL Rating Recognized Agency/Standard CSA, UL Approved Standards UL Flammability Rating UL P4V-0 | Operating Temperature Range | -65 – 105 °C[-85 – 221 °F] |
| Circuit Application Industry Standards UL Rating Recognized Agency/Standard CSA, UL Approved Standards CSA LR7189, UL E28476 UL Flammability Rating UL 94V-0 | Operation/Application | |
| Industry Standards UL Rating Recognized Agency/Standard CSA, UL Approved Standards CSA LR7189, UL E28476 UL Flammability Rating UL 94V-0 | Solder Process Feature | Solder Dipped |
| UL Rating Recognized Agency/Standard CSA, UL Approved Standards CSA LR7189, UL E28476 UL Flammability Rating UL 94V-0 | Circuit Application | Signal |
| Agency/Standard CSA, UL Approved Standards CSA LR7189, UL E28476 UL Flammability Rating UL 94V-0 | Industry Standards | |
| Approved Standards CSA LR7189, UL E28476 UL 94V-0 | UL Rating | Recognized |
| UL Flammability Rating UL 94V-0 | Agency/Standard | CSA, UL |
| | Approved Standards | CSA LR7189, UL E28476 |
| | UL Flammability Rating | UL 94V-0 |
| Packaging Features | Packaging Features | |
| Packaging Quantity 180 | Packaging Quantity | 180 |

Product Compliance

Packaging Method

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|--|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Wave solder capable to 265°C |
| | |

Box & Tray, Tray


Product Compliance Disclaimer




This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts







Customers Also Bought



TE Part #211400-1 Cable/Panel Mount Connector, CPC Series 1















Documents

Product Drawings
08 DIP PLUG CONN-W/COVER

English

CAD Files

3D PDF

Ribbon Cable Connectors, Wire-to-Board, 8 Position, 2.54 mm [.1 in] Centerline, Vertical, Through Hole - Solder, 2 Row, Plug, Standard Profile



3D

Customer View Model

ENG_CVM_CVM_746611-7_G.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_746611-7_G.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_746611-7_G.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Ribbon Cable Interconnect Solutions

English

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

UL Report

English