



MJ8-POE-A



- POE++ Mode A compatible Surge Protector
- Cat. 5e compatible
- Shielded RJ45 connectors
- 16 kA maximum surge discharge capability
- Max Transmission up to 1Gbps
- Max Bandwidth up to 100 MHz
- UL497B



	Electrical Characteristics																																								
 <p>P: 3-electrode GDT DBC: Low capacitance diode</p>	<table border="1"> <tbody> <tr><td>Insertion loss</td><td></td><td>< 1 dB</td></tr> <tr><td>Impulse current 2 x 10/350µs Test - D1 Category</td><td>limp</td><td>500 A</td></tr> <tr><td>NOMINAL DC LINE VOLTAGE</td><td>Vdc</td><td>48</td></tr> <tr><td>MAX. DC LINE VOLTAGE</td><td>Vdc</td><td>60</td></tr> <tr><td>WIRES</td><td></td><td>8W+Shield+Ground</td></tr> <tr><td>LINE CURRENT MAX</td><td>(A)</td><td>1.6</td></tr> <tr><td>POWER RATING</td><td>(W)</td><td>100</td></tr> <tr><td>AMBIENT MIN</td><td>(C)</td><td>-40</td></tr> <tr><td>AMBIENT MAX</td><td>(C)</td><td>+85</td></tr> <tr><td>PROTECTION LEVEL</td><td>(V)</td><td>70</td></tr> <tr><td>IMAX8/20µs</td><td>(kA)</td><td>16</td></tr> <tr><td>MAX. DATA RATE</td><td>Gbps</td><td>1</td></tr> <tr><td>MAX. FREQUENCY</td><td>Mhz</td><td>100</td></tr> </tbody> </table>	Insertion loss		< 1 dB	Impulse current 2 x 10/350µs Test - D1 Category	limp	500 A	NOMINAL DC LINE VOLTAGE	Vdc	48	MAX. DC LINE VOLTAGE	Vdc	60	WIRES		8W+Shield+Ground	LINE CURRENT MAX	(A)	1.6	POWER RATING	(W)	100	AMBIENT MIN	(C)	-40	AMBIENT MAX	(C)	+85	PROTECTION LEVEL	(V)	70	IMAX8/20µs	(kA)	16	MAX. DATA RATE	Gbps	1	MAX. FREQUENCY	Mhz	100	
Insertion loss		< 1 dB																																							
Impulse current 2 x 10/350µs Test - D1 Category	limp	500 A																																							
NOMINAL DC LINE VOLTAGE	Vdc	48																																							
MAX. DC LINE VOLTAGE	Vdc	60																																							
WIRES		8W+Shield+Ground																																							
LINE CURRENT MAX	(A)	1.6																																							
POWER RATING	(W)	100																																							
AMBIENT MIN	(C)	-40																																							
AMBIENT MAX	(C)	+85																																							
PROTECTION LEVEL	(V)	70																																							
IMAX8/20µs	(kA)	16																																							
MAX. DATA RATE	Gbps	1																																							
MAX. FREQUENCY	Mhz	100																																							
	Mechanical Characteristics																																								
	<table border="1"> <tbody> <tr><td>Weight</td><td></td><td>0.120 kg</td></tr> <tr><td>TECHNOLOGY</td><td></td><td>SAD-GDT</td></tr> <tr><td>NETWORK CONFIGURATION</td><td></td><td>Single POE Line</td></tr> <tr><td>CONNECTOR TYPE</td><td></td><td>Shielded RJ45</td></tr> <tr><td>PIN OUT</td><td></td><td>[1-2][3-6][4-5][7-8]</td></tr> <tr><td>NEMA RATING (IP RATING)</td><td></td><td>NEMA 2 (IP20)</td></tr> <tr><td>DIMENSIONS</td><td></td><td>See diagram</td></tr> </tbody> </table>	Weight		0.120 kg	TECHNOLOGY		SAD-GDT	NETWORK CONFIGURATION		Single POE Line	CONNECTOR TYPE		Shielded RJ45	PIN OUT		[1-2][3-6][4-5][7-8]	NEMA RATING (IP RATING)		NEMA 2 (IP20)	DIMENSIONS		See diagram																			
Weight		0.120 kg																																							
TECHNOLOGY		SAD-GDT																																							
NETWORK CONFIGURATION		Single POE Line																																							
CONNECTOR TYPE		Shielded RJ45																																							
PIN OUT		[1-2][3-6][4-5][7-8]																																							
NEMA RATING (IP RATING)		NEMA 2 (IP20)																																							
DIMENSIONS		See diagram																																							
	Standards																																								
	<table border="1"> <tbody> <tr><td>Certification</td><td></td><td>UL 497B</td></tr> <tr><td>UL STANDARD</td><td></td><td>UL497B</td></tr> <tr><td>UL CATEGORY</td><td></td><td>QVGQ</td></tr> <tr><td>UL FILE NUMBER</td><td></td><td>E184939</td></tr> <tr><td>STANDARDS</td><td></td><td>NOM-003-SCFI-2014, NOM-001-SCFI-1993</td></tr> <tr><td>ENVIRONMENTAL STANDARDS</td><td></td><td>ROHS</td></tr> </tbody> </table>	Certification		UL 497B	UL STANDARD		UL497B	UL CATEGORY		QVGQ	UL FILE NUMBER		E184939	STANDARDS		NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS		ROHS																						
Certification		UL 497B																																							
UL STANDARD		UL497B																																							
UL CATEGORY		QVGQ																																							
UL FILE NUMBER		E184939																																							
STANDARDS		NOM-003-SCFI-2014, NOM-001-SCFI-1993																																							
ENVIRONMENTAL STANDARDS		ROHS																																							
	Part number																																								
	581519																																								