



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₀	RELEASED	1-8-90	<i>DeComelis</i>

HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER ASTM-A380
SPRING WASHER		
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457, MIL-P-19468, AND FED. SPEC L-P-403	N/A
CENTER CONTACT	BERYLLIUM COPPER PER QQ-C-530, ALLOY 173	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
CONTACT SLEEVE		
RETAINING RING	BERYLLIUM COPPER PER QQ-C-533	NICKEL PLATE PER QQ-N-290 OVER COPPER PLATE PER MIL-C-14550
RETAINING RING CONTACT FINGERS	BERYLLIUM COPPER PER QQ-C-533	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
SHRINK TUBING	HEAT SHRINKABLE POLYOLEFIN COMPOUND MIL-I-23053-4	N/A
FERRULE	SOFT COPPER ALLOY	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550

COMPONENT	MATERIAL	FINISH
-----------	----------	--------

CABLE ENTRY DIAMETER MINIMUM	
CONTACT	.021
HOUSING	.062

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON

FRAC.	DEC.	ANGLES
± 1/64	± .005	± °

These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.

DRAWN BY L. ROSS DATE 1-4-90
 CHECKED BY M.Y. 1-5-89
 APP'D BY *DeComelis* 1-8-90



AMP Incorporated
 140 Fourth Avenue
 Waltham, MA 02451-7599

USE ASS'Y PROCEDURE
 408-08304
 NO. AP. (47-022)

TITLE			
OSSP FLOATING FLANGE MOUNT CABLE JACK-CRIMP ATTACHMENT			
SIZE	CODE IDENT NO.		REV
B	26805	4736-5001-02	01 ₀
SCALE	4:1		SHEET 1 OF 1

- NOTES:
- DESIGNED FOR USE WITH RG316 FLEXIBLE CABLE
 - CAPTURED CENTER CONTACT

RECOMMENDED MOUNTING DIMS.