

## Disconnect terminal block - ST 2,5-TG RD - 3038436

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



The illustration shows the gray version

Disconnect terminal block, Connection type: Spring-cage connection, Cross section: 0.08 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 28 - 12, Nominal current: 20 A, Nominal voltage: 400 V, Length: 60.5 mm, Width: 5.2 mm, Color: red, Assembly: NS 35/7,5, NS 35/15



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 50 pc    |
| Weight per Piece (excluding packing) | 7.6 g    |
| Custom tariff number                 | 85369010 |
| Country of origin                    | Germany  |

### Technical data

#### General

|  |   |
|--|---|
| Number of levels                       | 1   |
| Number of connections                  | 2   |
| Nominal cross section                  | 2.5 mm <sup>2</sup>                                   |
| Color                                  | red   |
| Insulating material                    | PA  |
| Flammability rating according to UL 94 | V0  |
| Rated surge voltage                    | 6 kV  |
| Degree of pollution                    | 3   |
| Overvoltage category                   | III   |
| Insulating material group              | I   |
| Connection in acc. with standard       | IEC 60947-7-1   |
| Nominal current I <sub>N</sub>         | 20 A (current is determined by the plug used)         |
| Maximum load current                   | 20 A (with 4 mm <sup>2</sup> conductor cross section) |

## Disconnect terminal block - ST 2,5-TG RD - 3038436

### Technical data

#### General

|   |  |
|---|--|
| Nominal voltage $U_N$   | 400 V (voltage is determined by the plug used) |
| Open side panel   | Yes  |
| Shock protection test specification   | DIN EN 50274 (VDE 0660-514):2002-11            |
| Back of the hand protection   | guaranteed                                     |
| Finger protection   | guaranteed                                     |
| Result of surge voltage test  | Test passed                                    |
| Surge voltage test setpoint   | 7.3 kV   |
| Result of power-frequency withstand voltage test  | Test passed                                    |
| Power frequency withstand voltage setpoint  | 1.89 kV  |
| Result of the test for mechanical stability of terminal points (5 x conductor connection) | Test passed                                    |
| Result of bending test  | Test passed                                    |
| Bending test rotation speed   | 10 rpm   |
| Bending test turns  | 135  |
| Bending test conductor cross section/weight   | 0.08 mm <sup>2</sup> / 0.1 kg                  |
|   | 2.5 mm <sup>2</sup> / 0.7 kg                   |
|   | 4 mm <sup>2</sup> / 0.9 kg                     |
| Tensile test result   | Test passed                                    |
| Conductor cross section tensile test  | 0.08 mm <sup>2</sup>                           |
| Tractive force setpoint   | 5 N  |
| Conductor cross section tensile test  | 2.5 mm <sup>2</sup>                            |
| Tractive force setpoint   | 50 N   |
| Conductor cross section tensile test  | 4 mm <sup>2</sup>                              |
| Tractive force setpoint   | 60 N   |
| Result of tight fit on support  | Test passed                                    |
| Tight fit on carrier  | NS 35  |
| Setpoint  | 1 N  |
| Result of voltage-drop test   | Test passed                                    |
| Requirements, voltage drop  | ≤ 6,4 mV                                       |
| Result of temperature-rise test   | Test passed                                    |
| Short circuit stability result  | Test passed                                    |
| Conductor cross section short circuit testing   | 2.5 mm <sup>2</sup>                            |
| Short-time current  | 0.3 kA   |
| Result of aging test  | Test passed                                    |
| Ageing test for screwless modular terminal block temperature cycles                       | 192  |
| Result of thermal test  | Test passed                                    |
| Proof of thermal characteristics (needle flame) effective duration                        | 30 s   |

## Disconnect terminal block - ST 2,5-TG RD - 3038436

### Technical data

#### General

|  |  |
|--|--|
| Oscillation, broadband noise test result         | Test passed                                    |
| Test specification, oscillation, broadband noise | DIN EN 50155 (VDE 0115-200):2008-03            |
| Test spectrum                                    | Service life test category 2, bogie mounted    |
| Test frequency                                   | $f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$ |
| ASD level  | $6.12 \text{ (m/s}^2\text{)}^2\text{/Hz}$      |
| Acceleration                                     | 3.12 g   |
| Test duration per axis                           | 5 h  |
| Test directions                                  | X-, Y- and Z-axis                              |
| Shock test result                                | Test passed                                    |
| Test specification, shock test                   | DIN EN 50155 (VDE 0115-200):2008-03            |
| Shock form                                       | Half-sine                                      |
| Acceleration                                     | 30g  |
| Shock duration                                   | 18 ms  |
| Number of shocks per direction                   | 3  |
| Test directions                                  | X-, Y- and Z-axis (pos. and neg.)              |

#### Dimensions

|                  |         |
|------------------|---------|
| Width            | 5.2 mm  |
| Length           | 60.5 mm |
| Height NS 35/7,5 | 36.5 mm |
| Height NS 35/15  | 44 mm   |

#### Connection data

|   |                        |
|---|------------------------|
| Conductor cross section solid min.  | 0.08 mm <sup>2</sup>   |
| Conductor cross section solid max.  | 4 mm <sup>2</sup>      |
| Conductor cross section flexible min.   | 0.08 mm <sup>2</sup>   |
| Conductor cross section flexible max.   | 2.5 mm <sup>2</sup>    |
| Conductor cross section AWG min.  | 28                     |
| Conductor cross section AWG max.  | 12                     |
| Conductor cross section flexible, with ferrule without plastic sleeve min.              | 0.14 mm <sup>2</sup>   |
| Conductor cross section flexible, with ferrule without plastic sleeve max.              | 2.5 mm <sup>2</sup>    |
| Conductor cross section flexible, with ferrule with plastic sleeve min.                 | 0.14 mm <sup>2</sup>   |
| Conductor cross section flexible, with ferrule with plastic sleeve max.                 | 2.5 mm <sup>2</sup>    |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 0.5 mm <sup>2</sup>    |
| Connection method   | Spring-cage connection |
| Stripping length  | 8 mm ... 10 mm         |
| Internal cylindrical gage   | A3                     |

# Disconnect terminal block - ST 2,5-TG RD - 3038436

## Technical data

### Standards and Regulations

|  |               |
|--|---------------|
| Connection in acc. with standard       | IEC 60947-7-1 |
| Flammability rating according to UL 94 | V0            |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141120 |
| eCl@ss 4.1 | 27141120 |
| eCl@ss 5.0 | 27141120 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141126 |
| eCl@ss 8.0 | 27141126 |
| eCl@ss 9.0 | 27141126 |

### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC000897 |
| ETIM 5.0 | EC000902 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

## Approvals

### Approvals

---

Approvals

EAC / RS

---

Ex Approvals

---

Approvals submitted

## Disconnect terminal block - ST 2,5-TG RD - 3038436

### Approvals

---

#### Approval details

EAC

RS

### Drawings

#### Circuit diagram

