

# Off-the-Shelf MX150 Cable Assemblies

**molex**

Off-the-Shelf MX150 Cable Assemblies deliver a 22.0A current rating and offer a variety of cable lengths for automotive and commercial vehicle applications

## Features and Advantages

### Mat seal technology for MX150 (1.50mm) terminals

Eliminates the need for individual cable seals, which affords reduced package size and reduced cost

### 1-piece 3.50mm-pitch housing

Eliminates unnecessary and costly assembly Operations; offers a compact connector

### Preassembled terminal position assurance (TPA) housing

Ensures crimped terminal leads are properly locked into connector

### Grommet cap

Protects the mat seal and assures proper alignment of the terminals

### Flashover options (custom void patterns) available

Provides design flexibility

### Connector position assurance (CPA) option available

Assures connectors have been fully mated and prevents accidental disconnection

### 4 polarization and color options

Facilitates quick visual installation

### USCAR interface

Has a released and approved interface for major North America OEMs



MX150 Cable Assemblies

### Temperature class 4 (-40 to +125°C) and 22.0A current rating

Delivers superior performance

### V0 versions available (UL1977 certified)

Meets stringent safety requirements



### Conforms to USCAR-2/USCAR-21/GMW3191

Is for use in on-engine, high-vibration, under-hood and under-chassis environments at temperature class 4

# Off-the-Shelf MX150 Cable Assemblies



## Markets and Applications

### Automotive and Commercial Vehicles



- Transmissions
- Head/tail lamps
- Body harnesses
- Wipers, washers, defoggers
- Speedometers
- A/C modules
- Turn signals
- Airbag harnesses
- Speakers
- Door connectors
- Brake modules
- Horns
- Marine equipment

### Consumer/Home Appliances

- White goods
- LED lightings

### Industrial

- Automation equipment
- Process control equipment
- Construction equipment



# Off-the-Shelf MX150 Cable Assemblies



## Specifications

### REFERENCE INFORMATION

Packaging: Bulk (connectors); reels (terminals)  
 UL File No.: N/A  
 CSA File No.: N/A  
 Use With: 14 AWG  
 Insulation Diameter: 2.5mm  
 Designed In: Millimeters  
 RoHS: Yes  
 Halogen-Free: No  
 Glow Wire Compliant: No  
 IP Rating: IP67

### ELECTRICAL

Voltage (max.): 14V DC  
 Current (max.): Up to 22.0A  
 Contact Resistance (max.): 10 milliohms  
 Dielectric Withstanding Voltage: 1000V AC (unmate connectors for 1 minute between adjacent terminals and between terminals to ground)  
 Insulation Resistance (min.): 20 Megohms

### MECHANICAL

Terminal Insertion Force (max): 30N  
 Terminal Retention to Housing (min): 90N  
 Mating Force (max.): 75N  
 Unmating Force (min.): 110N  
 Durability (max.): 25 cycles

### PHYSICAL

Housing: SPS/nylon  
 Contact: Copper Alloy  
 Plating:  
 Contact Area – Tin  
 Underplating – Tin  
 Operating Temperatures: -40 to +125°C

\*Information is based on MX150 connector specifications

## Ordering Information

	Component	Circuits	Lengths (mm)
216280	Off-the-Shelf MX150 Cable Assemblies	2,3, 4 and 6	150, 300 and 600
216281			
216282			
216283			
216285			
216286			
216287			
216288			

Custom product	Description
<a href="#">Contact Molex</a>	Off-the-Shelf MX150 Custom Cable Assemblies

[www.molex.com/link/otscableassemblies.html](http://www.molex.com/link/otscableassemblies.html)

Molex is a registered trademark of Molex, LLC in the United States of America and may be registered in other countries; all other trademarks listed herein belong to their respective owners.