		TOP	P VIEW	SIDE V	ΊEW					
	<u>Ø15±0.1</u>		Ø20±0.10		0.2±0.1					
				1						
Spe	ecifications			۲ <u>ــــــــــــــــــــــــــــــــــــ</u>			Revisio	on History		
Spe Description	ecifications Value	Unit	No	٦	Version		Revisio Description	-	Date	Approved
		Unit (Hz)	No 1) All dimensions are in mm unle		Version 1	Release		-	Date 10/21/2013	Approved J.S
Description	Value				+	Release	Description	-		
Description Resonant Frequency	Value 3,600	(Hz) (Ohm) (V)	1) All dimensions are in mm unle		+	Release	Description	-		
Description Resonant Frequency Resonant Impedance (Max)	Value 3,600 300	(Hz) (Ohm)	1) All dimensions are in mm unle		+	Release	Description	-		
Description Resonant Frequency Resonant Impedance (Max) Max Input Voltage	Value 3,600 300 30	(Hz) (Ohm) (V)	1) All dimensions are in mm unle		+	Release	Description	-		
Description Resonant Frequency Resonant Impedance (Max) Max Input Voltage Capacitance	Value 3,600 300 30 24,000	(Hz) (Ohm) (V)	1) All dimensions are in mm unle		+	Release	Description	-		
Description Resonant Frequency Resonant Impedance (Max) Max Input Voltage Capacitance Plate Material	Value 3,600 300 30 24,000 Brass	(Hz) (Ohm) (V) (pF)	1) All dimensions are in mm unle		+	Release	Description	-		
Description Resonant Frequency Resonant Impedance (Max) Max Input Voltage Capacitance Plate Material Operating Temperature	Value 3,600 300 30 24,000 Brass -20~+60	(Hz) (Ohm) (V) (pF) °C	1) All dimensions are in mm unle		+	Release	Description	-		

Additional considerations can be found at www.dbunlimitedco.com/technical-articles.