



Connectors > D-Shaped Connectors > D-Sub Connectors > IDC D-Sub Connectors > IDC D-Sub: Receptacle Kit, Wire to Wire, Signal, 2.74 mm



Connector & Housing Type: **Receptacle**

Solid Wire Size: **.13 – .32 mm<sup>2</sup>**

Shielded: **Yes**

Connector System: **Cable-to-Cable**

[All IDC D-Sub: Receptacle Kit, Wire to Wire, Signal, 2.74 mm \(8\)](#)

## Features

### Product Type Features

Shell Material Configuration	Front Metal Shell
Connector & Housing Type	Receptacle
Connector System	Cable-to-Cable
Connector Product Type	Connector Kit
Connector Shell Size	1
Connector & Contact Terminates To	Wire & Cable

### Configuration Features

Number of Positions	9
Number of Rows	2
Compatible With Wire & Cable Type	Discrete Wire, Round Jacketed Cable

### Body Features

Insert Material	Thermoplastic
Mating Retention Feature Material	Zinc Alloy
Cable Exit Angle	180°
Shield Plating Material	Tin
Shield Material	Steel
Shell Plating Material	Tin

### Contact Features

Contact Type	Socket
--------------	--------



Wire Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material	Gold Flash
Contact Underplating Material	Nickel
Contact Base Material	Phosphor Bronze
Contact Size	Size 20
Contact Current Rating (Max)	5 A

### Termination Features

Termination Method to Wire & Cable	Insulation Displacement (IDC)
------------------------------------	-------------------------------

### Mechanical Attachment

Mating Retention	With
Wire Insulation Support	With
Mating Retention Type	Jackscrew
Thread Size	4-40
Connector Mounting Type	Cable Mount (Free-Hanging)

### Housing Features

Shell Material	Steel
Centerline (Pitch)	2.77 mm[.109 in]

### Dimensions

Accepts Cable Diameter (Max)	9.53 mm[.375 in]
Accepts Cable Insulation Diameter Range	4.83 – 9.53 mm[.19 – .375 in]
Compatible Insulation Diameter Range	1.52 mm[.06 in]
Solid Wire Size	.13 – .32 mm <sup>2</sup>
Wire Size	.15 – .4 mm <sup>2</sup>

### Usage Conditions

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
-----------------------------	----------------------------

### Operation/Application

Shielded	Yes
Circuit Application	Signal

### Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

### Packaging Features

Packaging Quantity	1
--------------------	---



## Packaging Method

## Package

## Other

## D-Shaped Connectors Comment

Maximum cable diameter after jacket and braid removed., There is a maximum Cable O.D. of 9.02 [.355] for Shielding Enclosure Expansion Tool 58241-4.

## Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

## EU RoHS Directive 2011/65/EU

Compliant

## EU ELV Directive 2000/53/EC

Compliant

## China RoHS 2 Directive MIIT Order No 32, 2016

No Restricted Materials Above Threshold

## EU REACH Regulation (EC) No. 1907/2006

Current ECHA Candidate List: JUNE 2023 (235)  
Candidate List Declared Against: JAN 2023 (233)  
Does not contain REACH SVHC

## Halogen Content

Not Low Halogen - contains Br or Cl > 900 ppm.

## Solder Process Capability

Not applicable for solder process capability

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

## Compatible Parts



TE Part # CAT-AM7-248H4  
IDC D-Sub: Connector Kit, Plug, Wire to Wire, Signal, 2.77 mm

TE Part # CAT-023-DPARS1274  
D-Sub Plug Assembly: Standard, Right Angle, Shell Size 1, 2.74mm

TE Part # CAT-025-DPAVS1274  
D-Sub Plug Assembly: Standard, Vertical, Shell Size 1, 2.74mm

TE Part # 2-745492-0  
PLUG ASSY,9P,HDE,MS

TE Part # 58074-1  
MTA 50/100/156 MANUAL TOOL FRAME

TE Part # 608868-1  
HDE HT PKG FOR SUB D

TE Part # 205865-1  
09 PLUG RA/MS STD

### Also in the Series | AMPLIMITE HDE

Crimp D-Sub Connectors(1)

D-Sub Connector Contacts(13)

IDC D-Sub Connectors(75)

Insertion & Extraction Tools(2)

### Customers Also Bought

TE Part #1-796404-1  
CPC PSTD RCPT,17-16,R/A LF

TE Part #5499786-3  
A/L UNIV HDR 16P RA LG LAT

TE Part #5767096-1  
MICT,REC,038,ASY,.025,TAPE PKG

TE Part #2-1617031-3  
HFW1201K46 = M39016/6-209L

TE Part #1-87456-2  
16 MODIV HSG DR MRKD .100CL

TE Part #1-1879350-5  
RR01 5% R82 AMMO

TE Part #222006-1  
RECEPTACLE,PRESS FIT,COML BNC

TE Part #1734328-1  
Mini USB AB R/A,Rcpt,SMT,TRAY



## Documents

### Product Drawings

[KIT,RCPT,9P,HDE,SHLD ENCLSRE](#)

English

### CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG\\_CVM\\_CVM\\_1-747943-7\\_N.2d\\_dxf.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_1-747943-7\\_N.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_1-747943-7\\_N.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

### Datasheets & Catalog Pages

[AMPLIMITE Subminiature D Connectors - Cable Connectors](#)

English

[AMPLIMITE Cable Connectors and Shielding Hardware Kits QRG](#)

English

### Product Specifications

[Application Specification](#)

English

[Application Specification](#)

English

### Instruction Sheets

[Instruction Sheet \(U.S.\)](#)

English

[Instruction Sheet \(U.S.\)](#)

English



**Agency Approvals**

**UL Report**

English

**UL Report**

English