



Notes

1. **Material:**
 Insulator: PBT+30%G.F UL 94V-0
 Contact: Brass
 Shell: Spcc
2. **Mechanical:**
 Mating: 35N max.
 Withdrawal Force: 10N min.
 Durability: 1500 cycles min.
3. **Electrical:**
 Current-max[amps]: 1.5A
 Voltage-max[volts]: 30V
 Withstanding Voltage: 500V AC.
 Contact Resistance [ohms]: 30mΩ max.
 Insulation Resistance [ohms]: 1000MΩ min.
4. **Plating:**
 Contacts: Gold 1U" And Tin Over Nickel Plated.
 Shell: Nickel Over all Plating
5. **Environmental:**
 Temperature Range: -55°C to +85°C

12 1- 04 1 1 N X XX 05
 HOUSING COLOR:
 01=WHITE 02=BLACK
 PLATING GOLD:
 A=1u" B=3u"
 F=30u"

2012/03/29	XIE		NEW DWG		AO
DATE	DR.BY	ECN.NO.	DESCRIPTION	MARK	VER.
-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参考表			CnC Tech,LLC		
			TITLE: USB 4P A/M Solder G/F		
X.X	±0.30	X.X'	±3.00'	APPD:	PRODUCT NO: 1001-022-01300
X.XX	±0.20	X.XX'	±1.00'	CHECK:	DATE
X.XXX	±0.10	X.XXX'	±0.500'	DRAW:	SCALE
			2012/03/29 1:1 mm Z 1/1		