

1469001-1 ✓ ACTIVE

Z-PACK | Z-PACK HM-Zd


TE Internal #: 1469001-1

High Speed Backplane Connectors, 80 Position, Mating Alignment, Polarization Mating Alignment Type, 8 Row, 10 Column, Z-PACK HM-Zd

[View on TE.com >](#)



Connectors > PCB Connectors > Backplane Connectors > High Speed Backplane Connectors



Connector System: **Board-to-Board**

Number of Positions: **80**

Row-to-Row Spacing: **1.5 mm [.059 in]**

Mating Alignment: **With**

Mating Alignment Type: **Polarization**

Features

Product Type Features

Connector System	Board-to-Board
PCB Connector Assembly Type	PCB Mount Receptacle
Shroud Style	Fully Shrouded
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Pairs per Column	4
Number of Ground Positions	40
Card Slot Centerline	25.4 mm[1 in]
Number of Pairs	40
Number of Signal Positions	80
Number of Positions	80
Number of Rows	8
Number of Columns	10
PCB Mount Orientation	Right Angle



Guide Location	Unguided
----------------	----------

Electrical Characteristics

Operating Voltage	250 VAC
-------------------	---------

Signal Characteristics

Data Rate	≤12 Gb/s
-----------	----------

Body Features

Shield Material	Phosphor Bronze
-----------------	-----------------

Primary Product Color	Gray
-----------------------	------

Contact Features

Contact Layout	Matrix
----------------	--------

Contact Type	Receptacle
--------------	------------

Contact Mating Area Plating Material Thickness	.76 μm[30 μin]
--	----------------

Contact Mating Area Plating Material	Gold
--------------------------------------	------

Contact Base Material	Copper Nickel Silicon
-----------------------	-----------------------

Contact Current Rating (Max)	.7 A
------------------------------	------

Termination Features

Termination Post & Tail Length	2.2 mm[.086 in]
--------------------------------	-----------------

Termination Method to Printed Circuit Board	Through Hole - Press-Fit
---	--------------------------

Mechanical Attachment

Mating Alignment	With
------------------	------

Mating Alignment Type	Polarization
-----------------------	--------------

Connector Mounting Type	Board Mount
-------------------------	-------------

Housing Features

Housing Material	Polyester - GF
------------------	----------------

Centerline (Pitch)	2.5 mm[.098 in]
--------------------	-----------------

Dimensions

Connector Length	24.9 mm[.98 in]
------------------	-----------------

Connector Height	19.35 mm[.761 in]
------------------	-------------------

Connector Width	27.9 mm[1.098 in]
-----------------	-------------------

Row-to-Row Spacing	1.5 mm[.059 in]
--------------------	-----------------

Usage Conditions



Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Signal
---------------------	--------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Method	Tube
------------------	------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Pb (13% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 1469002-1
HM-ZD 4PR HDR 80P 5.2MM



TE Part # 6469002-1
HM-ZD 4PR HDR 80P 5.2MM



TE Part # 6469048-1
HMZD 4PR RA HDR 80P ASSY LF



TE Part # 1469074-1
HM-ZD 4PR HDR ASSY 1.8MM



TE Part # 6469074-1
HM-ZD 4PR HDR ASSY 1.8MM



TE Part # 91347-1
SEATING TOOL, HMZD RCPT, 4 PAIR



TE Part # 6469002-2
HM-ZD 4PR HDR 80P 3.7MM



TE Part # 6469046-1
HMZD HRD ASSY, 4 PAIR




TE Part # 6469056-1
HMZD 4PR. HDR ASSY., 25MM MODUL



TE Part # 6469079-1
HMZD HDR ASSY 4 PR SELECT LOAD



TE Part # 6469292-1
HM ZD 4 PR HEADER, SEQUENCED



TE Part # 1583224-1
TOOL, REMOVAL, HMZD RECEPT. HOUS



TE Part # 1583248-1
TOOL, REMOVAL, HMZD CHICLET, 4 PR




TE Part # 6469320-1
HM Zd 4 PR Pin Assy, Sequenced, LF


Also in the Series | **Z-PACK HM-Zd**



Hard Metric Backplane Connectors(1)



High Speed Backplane Connectors(46)



Insertion & Extraction Tools(2)

Customers Also Bought



TE Part #2201855-1
MINI I/O PLUG KIT TYPE I L



TE Part #5646445-1
2MM HM,ASY,T-E,REC,TWIST TULIP



TE Part #794236-1
04P CMNL HDR ASSY V0



TE Part #2007198-2
SFP+ 1x1 Cage Assembly, Press-Fit



TE Part #4-1879208-9
CPF 0402 1K0 0.1% 25PPM 1K RL



TE Part #2172034-1
MINI USB B, RCPT, R/A, T/H, PBT, Tray



TE Part #87232-3
03 MODII HDR SRRA UNSHRD .100



TE Part #1747981-1
Std HDMI, RA, SMT



TE Part #8-102898-4
02 MODII HDR SRST UNSHRD A/PIN

Documents

Product Drawings

[HM-ZD 4PR RECP 80P](#)

English

CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_1469001-1_H.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1469001-1_H.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1469001-1_H.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications



[Application Specification](#)

English

[Instruction Sheets](#)

[EXTRACTION TOOL FOR HM-Zd CONN.\(REC\)\(TOOL P/N: 1596027-1\)](#)

English

[Instruction Sheet \(non U.S.\)](#)

English