Lockout cap; 12-pole, separable; for sockets; Plastic; black

www.wago.com/770-201



Color:

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/770-201



Item description

Cover WINSTA® MIDI 12-pole

Implement the electrical installation effortlessly: The cover from the *WINSTA®* MIDI product line is the solution for error-free electrical installation. An extensive range of accessories rounds out the WINSTA® product line from WAGO. The *WINSTA®* MIDI Pluggable Connection System with Pushin CAGE CLAMP® spring pressure connection technology facilitates exemplary electrification. Due to the integrated test slot, it is possible to check connections even when they are plugged in. This saves time, labor, and money.

Push-in CAGE CLAMP® spring pressure connection technology – pluggable installation instead of laborious screw connections!

The WINSTA® Pluggable Connection System allows pluggable electrical installation. This significantly reduces the need for servicing and lowers costs. Now you can also lower installation expenses without compromising quality and safety: The WINSTA® MIDI accessory reduces the need for servicing and prevents unnecessary downtime.

- pre-assembled versions
- fast, secure installation

Data

Connection data

Connection 1

Pole number 12

Mechanical Data

Suitable for socket; separable

Material Data

Note (material data)

Information on material specifications can be found here

ColorblackInsulation materialPolyamide (PA66)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/770-201



Flammability class per UL94	VO
Fire load	0.037 MJ
Weight	0.4 g

Environmental requirements

Processing temperature	-5 +40 °C
Continuous operating temperature	-35 +85 ℃
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

Product Group	20 (Winsta)
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 8.0	EC002863
ETIM 7.0	EC002863
PU (SPU)	100 pcs
Packaging type	bag
Country of origin	DE
GTIN	4017332755252
Customs tariff number	39269097900

Environmental Product Compliance

RoHS Compliance Status Compliant, No Exemption

Approvals / Certificates

General approvals

			Certificate
Logo	Approval	Additional Approval Text	name
	VDE	EN 61535	40029808
	VDE Prüf- und Zertifizierungsinstitut		

Downloads Documentation

Bid Text

770-201 2019 年2月19日 xml Download

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/770-201



X81 - Datei		2.6 kB	2.6 kB	
770-201	2015 年1月13日	doc	Download	
doc - Datei		22.0 kB		

CAD/CAE-Data

CAE data

ZUKEN Portal 770-201	URL	Download
WSCAD Universe 770-201	URL	Download
CAD data		
2D/3D Models 770-201	URL	Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 770-201 URL Download Lockout cap; 12-pole, separable; for sockets; Plastic; black

Installation Notes

Product family

WINSTA® MIDI

Show all products from the family

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.