Product data sheet Characteristics

ZCKJD31H7

Limit switch body, Limit switches XC Standard, ZCKJ, fixed, w/o display, 1NC+2 NO, snap action, 1/2"NPT



Main

Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch body
Device short name	ZCKJ
Body type	Fixed
Product Compatibility	XCKJ
Associated head	ZCKE21 ZCKE67 ZCKE23 ZCKE62 ZCKE65 ZCKE65 ZCKE64 ZCKE06 ZCKE05 ZCKE63 ZCKE63 ZCKE66 ZCKE68 ZCKE66 ZCKE66 ZCKE66 ZCKE66 ZCKE66 ZCKE619 ZCKE08 ZCKE61
Body Material	Metal
Cable entry	1 entry tapped for 1/2" NPT conduit
Number of poles	3
Contacts type and composition	1 NC + 2 NO
Contact operation	Snap action
Number of steps	1 1 position
Contacts material	Silver plated contacts

Complementary

Complementary	
Local display	Without
Electrical connection	Screw-clamp terminals 1 x 0.342 x 0.75 mm ²
Positive opening	With
Minimum actuation speed	0.01 m/min
[le] rated operational current	1.5 A 240 V, AC-15, B300 EN/IEC 60947-5-1 appendix A 0.1 A 250 V, DC-13, R300 EN/IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	6 A
[Ui] rated insulation voltage	400 V 3)IEC 60947-1 contact block 300 VCSA C22.2 No 14 contact block 300 VUL 508 contact block
Maximum resistance across terminals	0.25 mOhm IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	4 KV IEC 60664 4 kV IEC 60947-1
Short-circuit protection	6 A cartridge fuse gG
Electrical durability	5000000 Cycles, DC-13 120 V, 2 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 4 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 3 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C
Width	1.57 in (40 mm)
Height	3.03 in (77 mm)
Depth	1.73 in (44 mm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Net Weight	0.68 lb(US) (0.31 kg)
Terminals description ISO n°1	(21-22)NC (31-32)NC (13-14)NO
Environment	
IP Degree of Protection	IP66
IK degree of protection	IK07
Ambient air temperature for operation	-13158 °F (-2570 °C) standard environment
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Environmental characteristic	Standard environment
Ordering and shipping details	
Category	22411 - LIMIT SWITCHES,IEC,XCKJ
Discount Schedule	Т
GTIN	3389110225112
Nbr. of units in pkg.	1
Package weight(Lbs)	10.69 oz (303 g)
Returnability	Yes
Country of origin	FR
Packing Units Unit Type of Package 1	PCE
Package 1 Height	1.69 in (4.3 cm)
Package 1 width	3.46 in (8.8 cm)
Package 1 Length	1.77 in (4.5 cm)
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₽Yes
Environmental Disclosure	Product Environmental Profile
Contractual warranty	
Contractual warranty	

18 months

Warranty