## CUSTOMER PRODUCT SPECIFICATION SHEET

# RoHS Compliant


### CAB556RF: I-PEX MHF 4L PLUG + SMA STRAIGHT BULKHEAD JACK + Ø1.13MM CABLE - 6GHz

### SPECIFICATIONS:


- 1. I-PEX MHF 4L PLUG, P/N: 20565-001R-13.
- 2. Ø1.13MM COAXIAL CABLE, COLOR: BLACK
- 3. SMA STRAIGHT BULKHEAD JACK, GOLD PLATED, P/N: RFCT-SMA117-F13.

#### NOTES:


- 1. THE ORIENTATION OF CONNECTORS ON DRAWING IS FOR REFERENCE ONLY, IF THE ORDER IS LEFT BLANK THE CONNECTOR WILL NOT HAVE FIXED ORIENTATION.
- 2. FIXED ORIENTATION IS SUGGESTED FOR CABLE LENGTH 50MM TO 100MM. PLEASE SPECIFY THE FIXED ORIENTATIONS FROM THE ORDER CODE (F1, F2, ETC)
- 3. CONTACT GRAD CONN IF THE ORIENTATION YOU REQUIRE IS NOT SHOWN.
- 4. WORKING FREQUENCY RANGE: DC-6GHz.
- 5. OPERATING TEMPERATURE: -40°C TO +85°C
- 6. IMPEDANCE: 50 OHM








IPEX 4L PLUG DIMENSION



SMA JACK DETAIL DIMENSION



"L" LENGTH IN MM
eg: 100MM = 0100
(MIN. 0050, MAX. = 0400
STANDARD = 0100, 0150, 0200)
Tolerance: 50mm : ±2mm.
51-200mm: ±5mm.
201-400mm: ±7mm.

1 = Φ1.13MM CABLE, COLOR: BLACK

WASHER AND NUT OPTIONS:

BLANK = SEPERATELY PACKED (STANDARD)

A = ASSEMBLED WITH CONNECTOR

\_\_CABLE SIZE:

ORIENTATION OPTIONS:


HOW TO ORDER

CAB556RF - X X X X - X X - X - 1

BLANK = DOES NOT HAVE A FIXED ORIENTATION

F1 = MHF CONNECTION DOWN (L=50-200MM) F2 = MHF CONNECTION UP (L=50-200MM)

(SEE NOTES 1, 2, 3 AND DIAGRAMS FOR MORE INFORMATION)



RECOMMENDED SMA MOUNTING HOLE

Scale: NTS	THIRD ANGLE	Unstated Tolerances: .X N/A .XX N/A	Material
Drawn: NYW	$\rightarrow$	.XX N/A .XXX N/A ANGLES N/A	SEE NOTE
App'd: XXX	Title CABLE ASSEMBLY		NOT TO SCALE
Date: 7 APR. '23	Revision: 1.1		Unit: mm



Drawing Number:
CAB556RF

Sheet 1	of 1
Drawing C	E and O E