12 INCHES LENGTH



Connector A 132119 SMA Jack Straight Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 919-386P-51S MCX Plug Straight Brass Gold-Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

	Connector A			Cable		Connector B		
Part #: Description: Type: Gender: Body Type: Contact Typ Polarity: Impedance: Mounting: Body Materi Body Finish IP Rating: Contact Mat Contact Fini Max. Freq.: Booting:	132119 SMA BHD JK R SMA Jack Straight Solder Standard 50 Ohm Bulkhead - Rear Bulkhead - Rear Gold None rial: Beryllium Coppe	G174 RG188 RG316 500 Mount	Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 12 Inches	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	919-386P-51S MCX PLUG RG174 MCX Plug Straight Crimp Standard 50 Ohm Cable Brass Gold-Nickel None Brass Gold-Nickel None Brass Gold 6 GHz MCX Plug Straight 0°	RG188 RG316 50O	
Amphenol		THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.		BLE ED DF ING Part No:	SMA-ST-JK/MCX-ST-PL G174 12I		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	