


CJ3139KDW-G (Dual P-Channel)

RoHS Device




| V(BR)DSS | RDS(on)MAX | ID |
|----------|--------------------|--------|
| -20V | 520mΩ @ -4.5V | -0.66A |
| | 700mΩ @ -2.5V | |
| | 950mΩ(TYP) @ -1.8V | |

Features

- High-side switching.
- Low on-resistance.
- Low threshold.
- Fast switching speed.


Mechanical data

- Case: SOT-363, molded plastic.
- Terminals: Solderable per MIL-STD-750, method 2026.
- Weight: 0.006 grams (approx.).



Circuit Diagram

G : Gate
S : Source
D : Drain



Maximum Ratings (at Ta=25 °C unless otherwise noted)

| Parameter | Symbol | Value | Unit |
|---|------------------------|-------------|------|
| Drain-source voltage | V _{DSS} | -20 | V |
| Typ. Gate-source voltage | V _{GS} | ±12 | V |
| Drain current-continuous | I _{D(DC)} | -0.66 | A |
| Drain current-pulsed (Note 1) | I _{DM(pulse)} | -2.64 | A |
| Power dissipation (Note 2) | P _D | 150 | mW |
| Thermal resistance from junction to ambient | R _{θJA} | 833 | °C/W |
| Junction temperature range | T _J | -40 to +150 | °C |
| Storage temperature range | T _{STG} | -55 to +150 | °C |

Electrical Characteristics (at TA=25°C unless otherwise noted)

| Parameter | Symbol | Conditions | Min | Typ | Max | Unit |
|---|---------------|---|-------|------|----------|------------|
| On/Off States | | | | | | |
| Drain-source breakdown voltage | $V_{(BR)DSS}$ | $V_{GS} = 0V, I_D = -250\mu A$ | -20 | | | V |
| Gate threshold voltage (Note 3) | $V_{GS(th)}$ | $V_{DS} = V_{GS}, I_D = -250\mu A$ | -0.35 | | -1.1 | V |
| Gate-body leakage current | I_{GSS} | $V_{GS} = \pm 10V, V_{DS} = 0V$ | | | ± 20 | μA |
| Zero gate voltage drain current | I_{DSS} | $V_{DS} = -20V, V_{GS} = 0V$ | | | -1 | μA |
| Drain-source on-state resistance (Note 3) | $R_{DS(on)}$ | $V_{GS} = -4.5V, I_D = -1A$ | | | 520 | m Ω |
| | | $V_{GS} = -2.5V, I_D = -800mA$ | | | 700 | |
| | | $V_{GS} = -1.8V, I_D = -500mA$ | | 950 | | |
| Forward transconductance | g_{fs} | $V_{DS} = -10V, I_D = -540mA$ | 0.8 | | | S |
| Dynamic characteristics (Note 4) | | | | | | |
| Input capacitance | C_{iss} | $V_{DS} = -16V, V_{GS} = 0V$ $f = 1MHz$ | | | 170 | pF |
| Output capacitance | C_{oss} | | | | 25 | |
| Reverse transfer capacitance | C_{rss} | | | | 15 | |
| Switching time (Note 4) | | | | | | |
| Turn-on delay time | $t_{d(on)}$ | $V_{DD} = -10V, I_D = -200mA$ $V_{GS} = -4.5V, R_G = 10\Omega$ | | 9 | | nS |
| Rise time | t_r | | | 5.8 | | |
| Turn-off delay time | $t_{d(off)}$ | | | 32.7 | | |
| Fall time | t_f | | | 20.3 | | |
| Drain-source diode characteristics | | | | | | |
| Drain-source diode forward voltage (Note 3) | V_{SD} | $I_S = -0.5A, V_{GS} = 0V$ | | | -1.2 | V |

- Notes: 1. Repetitive rating: Pulse width limited by maximum junction temperature.
 2. This test is performed with no heat sink at Ta=25°C.
 3. Pulse test: Pulse width $\leq 300\mu s$, Duty cycle $\leq 0.5\%$.
 4. These parameters have no way to verify.

Rating and Characteristic Curves (CJ3139KDW-G)

Fig.1 - Output Characteristics




Fig.2 - Transfer Characteristics




Fig.3 - $R_{DS(ON)} - I_D$




Fig.4 - $R_{DS(ON)} - V_{GS}$




Fig.5 - $I_S - V_{SD}$









Fig.6 - Threshold Voltage



Company reserves the right to improve product design, functions and reliability without notice.

REV:B

Reel Taping Specification




| | SYMBOL | A | B | C | d | D | D1 | D2 |
|---------|--------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| SOT-363 | (mm) | 2.25 ± 0.05 | 2.55 ± 0.05 | 1.20 ± 0.05 | 1.50 ± 0.10 | 178.00 ± 2.00 | 54.40 ± 1.00 | 13.00 ± 1.00 |
| | (inch) | 0.089 ± 0.002 | 0.100 ± 0.002 | 0.047 ± 0.002 | 0.059 ± 0.004 | 7.008 ± 0.079 | 2.142 ± 0.039 | 0.512 ± 0.039 |

| | SYMBOL | E | F | P | P0 | P1 | W | W1 |
|---------|--------|---------------|---------------|---------------|---------------|---------------|----------------------|---------------|
| SOT-363 | (mm) | 1.75 ± 0.10 | 3.50 ± 0.10 | 4.00 ± 0.10 | 4.00 ± 0.10 | 2.00 ± 0.10 | 8.00 + 0.30/-0.10 | 12.30 ± 1.00 |
| | (inch) | 0.069 ± 0.004 | 0.138 ± 0.004 | 0.157 ± 0.004 | 0.157 ± 0.004 | 0.079 ± 0.004 | 0.315 + 0.012/-0.004 | 0.484 ± 0.039 |

Company reserves the right to improve product design , functions and reliability without notice.

Marking Code


| Part Number | Marking Code |
|-------------|--------------|
| CJ3139KDW-G | 39K |



Solid dot = Control code

Suggested P.C.B. PAD Layout

| SIZE | SOT-363 | |
|------|---------|--------|
| | (mm) | (inch) |
| A | 0.80 | 0.032 |
| B | 0.40 | 0.016 |
| C | 0.65 | 0.026 |
| D | 1.94 | 0.076 |
| E | 2.74 | 0.108 |



Standard Packaging

| Case Type | REEL PACK | |
|-----------|--------------|------------------|
| | REEL (pcs) | Reel Size (inch) |
| SOT-363 | 3,000 | 7 |