# 2170773-6 ACTIVE

#### zQSFP+/QSFP28

TE Internal #: 2170773-6

QSFP, QSFP+ & zQSPF+, Cage Assembly, 1 x 1, Internal/External EMI Springs, Included Lightpipe, Standard, Data Rate (Max) 28 Gb

/s, zQSFP+/QSFP28

View on TE.com >



Connectors > Pluggable IO Connectors & Cages > QSFP, QSFP+ & zQSPF+



Pluggable I/O Product Type: Cage Assembly

Port Matrix Configuration: 1 x 1

EMI Containment Feature Type: Internal/External EMI Springs

Included Lightpipe: Yes
Enhancements: Standard

#### **Features**

#### **Product Type Features**

Product Type Features	
Form Factor	QSFP28/56
Cage Type	Ganged
Pluggable I/O Product Type	Cage Assembly
Connector System	Cable-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Port Matrix Configuration	1 x 1
Number of Ports	1
Lightpipe Configuration	Quad Round
Number of Rear EONs per Port Column	0
Electrical Characteristics	
Data Rate (Max)	28 Gb/s
Contact Features	
PCB Contact Termination Area Plating Material	Tin

2.05 mm[.081 in]

**Termination Features** 

Termination Post & Tail Length



Termination Method to	Printed Circuit Board	Throug	h Hole - Press-Fit
-----------------------	-----------------------	--------	--------------------

#### **Mechanical Attachment**

### **Housing Features**

Cage Material	Nickel Silver	

#### **Dimensions**

PCB Thickness (Recommended)	1.57 mm[.062 in]	
-----------------------------	------------------	--

### **Usage Conditions**

Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
-----------------------------	---------------------------

### Operation/Application

Heat Sink Compatible	No
For Use With Pluggable I/O Products	QSFP28 Cable Assembly, QSFP28 MSA Compatible Transceiver
Pluggable I/O Applications	SFP+ Stacked Belly-to-Belly
Circuit Application	Signal

### **Industry Standards**

UL Flammability Rating	UL 94V-0	

### **Packaging Features**

Packaging Method Box & Tray	
-----------------------------	--

#### Other

EMI Containment Feature Type	Internal/External EMI Springs
Included Lightpipe	Yes
Enhancements	Standard

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2021 (211)



#### Does not contain REACH SVHC

Halogen Content	Not Low Halogen - contains Br or Cl > 900
	ppm.

Solder Process Capability

Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

# Compatible Parts











**QSFP28-Four SFP+ Cable Assembly:** 26 AWG



QSFP56 to QSFP56 Cable Assembly: 30 AWG



QSFP56-Two QSFP56 Cable Assembly: 30 AWG







26 AWG









# Also in the Series | zQSFP+/QSFP28





# Customers Also Bought





FIXED, REAR MOUNT SOCKET

CONNECTOR













### **Documents**

Product Drawings
CAGE ASSY, QSFP28 1X1, QUAD, LP

English

**CAD Files** 

3D PDF

3D



**Customer View Model** 

ENG\_CVM\_CVM\_2170773-6\_2.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2170773-6\_2.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2170773-6\_2.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

QSFP28/56 and zQSFP+ Interconnects

English

**Product Specifications** 

**Application Specification** 

English