

Specification Sheet

Part Number: 110-80004

Tensions and provides clean, flush cuts for 50lb. to 250lb. cable ties, including wide strap ties.

Impact-resistant housing and durable components for extended service life.



Easy-to-adjust tension knob offers 33 different settings for precise, repeatable applications.

Advanced ergonomic design minimizes necessary hand force and "kickback" to reduce repetitive-motion injuries.

EVO 9HT High Tension Mechanical Hand Tool, Tension Range 27 lb to 116 lb, 1/pkg

Article Number 110-80004

Type EVO9HT

Color Black (BK) Red (RD)

Quantity Per carton

Product Description

HellermannTyton's EVO 9 manual cable tie application tool combines durability, precision and control with unparalleled comfort. Manufactured with high-performance materials and components, the EVO 9 cuts cable ties with up to 250-lb tensile strength. Its innovative, ergonomic design minimizes the stress on hands and wrists and "kickback" that occur with traditional tools, reducing the risk of repetitive-motion injuries. The HT model offers high tension while the SP model features a smaller grip.

| Short Description | EVO 9HT High Tension Mechanical Hand Tool, Tension Range 27 lb to 116 lb, 1/pkg |
|--------------------------------|---|
| Global Part Name | EVO9HT-MET/PL-BK/RD |
| | |
| Length L (Imperial) | 7.5 |
| Length L (Metric) | 191 |
| Width W (Imperial) | 1.3 |
| Width W (Metric) | 33 |
| Cable Ties | T120, T150, T250, T255, WS |
| Height H (Imperial) | 5.3 |
| Height H (Metric) | 135 |
| Cable Tie Width Max (Imperial) | 0.5 |
| | |
| | |
| Material | Metal (MET) Plastic (PL) |
| Material Shortcut | MET PL |
| UV Resistant (Yes/No) | No |
| Reach Compliant (Article 33) | No |

| ROHS Compliant | Yes |
|-----------------------------|------------|
| | |
| Package Quantity (Imperial) | 1 |
| Package Quantity (Metric) | 1 |
| Customs Number | 8205599000 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions