


In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		TEST METHOD		REQUIREMENTS		QT	AT
OPERATING TEMPERATURE RANGE	-35°C T0 + 85°C (NOTE1)	STORAGE TEMPERATURE RANGE	-10°C T0 + 60°C (NOTE3)				
OPERATING HUMIDITY RANGE	20 % TO 80 % (NOTE2)	STORAGE HUMIDITY RANGE	40 % TO 70 % (NOTE3)				
VOLTAGE	AC/DC 100V	APPLICABLE CONNECTOR	DF50A-*S-1G				
CURRENT	AWG 28 : 1.0 A AWG 30 : 0.9 A	APPLICABLE CONTACT	DF50-2830SCFA				
SPECIFICATIONS							
ITEM	TEST METHOD	REQUIREMENTS					
CONSTRUCTION							
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.					
MARKING	CONFIRMED VISUALLY.						
ELECTRIC CHARACTERISTICS							
CONTACT RESISTANCE	AC 20mV MAX 1mA (DC OR 1000 Hz).	30mΩ MAX.	X				
INSULATION RESISTANCE	100V DC.	500MΩ MIN.	X				
VOLTAGE PROOF	300V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X				
MECHANICAL CHARACTERISTICS							
MECHANICAL OPERATION	30TIMES INSERTIONS AND EXTRACTIONS.	① CONTACT RESISTANCE: 50mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X				
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 10 CYCLE FOR EACH, FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X				
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.						
ENVIRONMENTAL CHARACTERISTICS							
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.	① CONTACT RESISTANCE: 50mΩ MAX. ② INSULATION RESISTANCE: 100MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X				
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55→+85°C 30 → 30min. UNDER 5 CYCLES. THE TRANSFERRING TIME OF THE TANK IS 2~3 min.	① CONTACT RESISTANCE: 50mΩ MAX. ② INSULATION RESISTANCE: 500MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X				
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE			
△							
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-346572-01				
 SPECIFICATION SHEET HIROSE ELECTRIC CO., LTD.		PART NO.	DF50A-*P-1H (51)				
		CODE NO.	CL665-				
APPROVED		KI. AKIYAMA		12.06.26			
CHECKED		HK. UMEHARA		12.06.26			
DESIGNED		ST. SATO		12.06.26			
DRAWN		ST. SATO		12.06.26			

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

SPECIFICATIONS


ITEM	TEST METHOD	REQUIREMENTS	QT	AT
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE, 245°C FOR INSERTION DURATION, 5 sec.	SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.	X	-
RESISTANCE TO SOLDERING HEAT	1) REFLOW SOLDERING «REFLOW AREA» MAX250°C WITHIN 10 sec MIN 220°C WITHIN 60 sec «PREHEATING AREA» 150~180°C 90~120s 2) MANUAL SOLDERING SOLDERING IPON TEMPERATURE 350±10°C SOLDERING TIME 3~4s. NO STRENGTH ON CONTACT.	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.	X	-

--	--	--	--	--

REMARKS

NOTE 1: INCLUDING THE TEMPERATURE RISE BY CURRENT.
 NOTE 2: NON-CONDENSING
 NOTE 3: APPLY TO THE CONDITION OF LONG TERM STORAGE FOR UNUSED PRODUCTS BEFORE PCB ON BOARD.
 AFTER PCB BOARD, OPERATING TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERIM STORAGE DURING TRANSPORTATION

Unless otherwise specified , refer to JIS C 5402.

Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-346572-01	
HRS	SPECIFICATION SHEET	PART NO.	DF50A-*P-1H(51)	
	HIROSE ELECTRIC CO., LTD.	CODE NO	CL665-	 2/2