

Housing - HC-D 7-TFL-57/O1M20G/PA BK - 1410673

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



HEAVYCON sleeve housing D7, for single locking latch, height 57 mm, with support, straight conductor exit, PA



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	22.0 g
Custom tariff number	85472000
Country of origin	Germany

Technical data

Dimensions

Height	57 mm
Width	28 mm
Length	26.5 mm

Ambient conditions

Degree of protection of housing (IP)	IP54
	IP65 (with sealing screw)
Ambient temperature (operation)	-40 °C ... 125 °C

General

Note	For contact inserts HC-D7, D8, A3, A4, B5, HS2-D7
Size	D7
Housing type	Sleeve housing
Color	black
Locking type	for single locking latch
No. of cable outlets	1
Cable exit	straight

Housing - HC-D 7-TFL-57/O1M20G/PA BK - 1410673

Technical data

General

Screw connection	none
Type of the screw connection	1x M20
Housing material	Polyamide

Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440202
eCl@ss 9.0	27440202

ETIM

ETIM 3.0	EC000437
ETIM 5.0	EC000437

UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

Approvals

Approvals

Approvals

EAC / GL

Ex Approvals

Housing - HC-D 7-TFL-57/O1M20G/PA BK - 1410673

Approvals

Approvals submitted

Approval details

EAC

GL

Drawings

Dimensional drawing

