

NOTES: (UNLESS OTHERWISE SPECIFIED)

1. MATERIAL:

1.1. CONTACT BODY: COPPER ALLOY.

1.2. POSITIONING CLIP: STAINLESS STEEL.

2. SPECIFICATIONS:

2.1 CURRENT RATING: 7.5A(MAX). 2.2 TERMINATION TYPE: CRIMPING.

2.3 CRIMP WIRE RANGE: 26~24AWG.

3. SUITABLE SOCKET TYPE: MP24W23xx.

4. ROHS COMPLIANT.

5. ALL DIMENSION ARE FOR REFERENCE USE ONLY.

REVISIONS						
REV	ECO	DESCRIPTION	DATE	BY	APPR	
B1	-	RELEASED DRAWING	JAN-18-2014	ARROW	TOMMY	
B2	-	ADDED MS24W23G5	JUL-28-2023	JUN	TOMMY	
В3	-	ADDED MS24W23T,MS24W23S	AUG-2-2023	JUN	TOMMY	

P/N	CONTACT PLATING(MATING AREA)		
MS24W23T	TIN PLATING OVER NICKEL.		
MS24W23S	SILVER PLATING OVER NICKEL.		
MS24W23F	GOLD FLASH PLATING OVER NICKEL.		
MS24W23G5	5μ"GOLD PLATING OVER NICKEL.		
MS24W23G10	10μ"GOLD PLATING OVER NICKEL.		
MS24W23G15	15μ"GOLD PLATING OVER NICKEL.		
MS24W23G30	30μ"GOLD PLATING OVER NICKEL.		

