



Premium 37

Professional Grade Vinyl Electrical Tape

Technical Data Sheet

October 2017

Description and Features

A 0,18 mm (7 mil) all weather, professional grade, pressure sensitive vinyl tape which applies easily and gives excellent performance over a wide range of temperatures. Cold and weather resistant. Flame retardant. Premium 111 can be used as primary insulation for splices up to 600 Volts. Use as protective outer jacket over splices and for all low temperature applications.

- Cold and weather resistant
- Flame retardant
- High dielectric strength
- Highly elastic
- Highly conformable
- High UV resistance
- Highly resistant to sun, water, oil, acids, alkalies, corrosive chemicals
- Meets ASTM D-3005, Type I; EN 60454-3-1, Type 11; UL 510; CSA C 22.2 no. 197; Meets 2000/53/EC and RoHS 2011/65/EU directives
- Pb, Cd, Hg, Cr (VI) free

Materials

Backing

PVC

Adhesive

Rubber based

Colors

Red, White, Blue, Yellow, Orange, Violet, Brown, Grey, Green

Standard Size

Width x Length

19 mm x 20 m (0.75 in. x 66 ft.)
Other sizes available upon request

Technical Properties

Characteristic

Specification

Typical Value

Test Method

Thickness, (mm)

0,18±0,025

0,175

ASTM D 1000

Breaking strength (N/cm)

26 min

30

ASTM D 1000

Elongation at break (%)

220 min

260

ASTM D 1000

Adhesion to steel (N/cm)

1,8 min

2,2

ASTM D 1000

Adhesion to backing (N/cm)

1,8 min

2,2

ASTM D 1000

Flammability (seconds)

4 max

0

ASTM D 1000

Flagging (mm)

3 max

0

ASTM D 1000

Temperature Rating (°C)

Maximum

80

80

UL510

105

105

CSA C 22.2 no.197

Minimum

-10

-10

UL510

-18

-18

CSA C 22.2 no 197

Dielectric Strength (kV)

-Standard

7 min

8

ASTM D 1000

-Wet

90%

7,2

ASTM D 1000

Dielectric Constant

--

3,2

ASTM D 150

Insulation Resistance (MΩ)

--

1x10⁶

ASTM D 1000

Recommended Uses

Used for general splicing purposes. Can be used as primary insulation for splices up to 600 Volts. Provide a protective outer jacket over splices for all low temperature applications. Can be used for wrapping wire harnesses, and insulating degaussing coils.

Storage

In original packaging, placed in horizontal position under cover and temperature between 5°C and 35 °C, 50-80% R.H.

Shelf Life

60 months from date of manufacture.

LIMITED WARRANTY: Plymouth warrants that its Product will substantially conform to that products written specifications for a period of one (1) year from the date of shipment, (Unless provided otherwise). Plymouth makes no warranty to the distributor, its customers, or the product's end user for the products merchantability and/or suitability for his/its intended use or purpose, and buyer shall assume all risks associated therewith. Provided that the product is proved to be defective within the terms described above, and provided buyer shall have first complied with all return policies of Plymouth, PLYMOUTH'S SOLE OBLIGATION AND BUYER'S EXCLUSIVE REMEDY UNDER THIS PRODUCT WARRANTY SHALL BE TO REPLACE SUCH QUANTITY OF THE PRODUCT AS IS PROVED TO BE DEFECTIVE WITHIN THE TIME PERIOD SPECIFIED ABOVE. EXCEPT AS EXPRESSLY SET FORTH HEREIN, PLYMOUTH MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED. In no event shall Plymouth be liable for collateral, consequential, indirect or incidental damages arising out of, or connected in any way with the supply of products. (Rev. 01/2017-2019)