



Directive 2002/95/EC  
 „RoHS“  
 Compliant

**Technical specification:**

Rated voltage: IEC 61076-2-101	4pos 250 V	5pos 60 V
Current rating: IEC 61076-2-101	4A at 40°C	
Insulation resistance: IEC 60512-2	>=10 GΩ	
Pollution degree: IEC 60664-1	3/2	
Degree of protection: IEC 60529	IP 67, in mated condition	
Temperature range: IEC 60664-1	-30°C ... +85°C	
Mating cycles: IEC 60512-9a	<=100	
Wire cross section:	AWG18 / max. 0,75mm²	

**Materials:**

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	PA6, UL 94
Screw:	Steel, nickel plated
Cable sealing:	Elastomere
O-Ring:	FPM
Coupling screw:	Die cast, nickel plated
Housing:	PA6 GF, UL 94

	Part no:	Description:	Pos:	Cable-Ø
Screw connection	43-00103	SAL - 12 - RSWC4 - S6/075	4	4 - 6mm
	43-00104	SAL - 12 - RSWC4 - S8/075	4	6 - 8mm
	43-00105	SAL - 12 - RSWC5 - S6/075	5	4 - 6mm
	43-00106	SAL - 12 - RSWC5 - S8/075	5	6 - 8mm

DO NOT ALTER CAD DRAWING BY HAND	Status: 19.01.09 db	dim. in mm	title: <b>Male connector M12x1, field attachable, angled, screw connection</b>								
	tolerance: ISO 2768-m	<table border="1" style="font-size: small;"> <tr> <td></td> <td>date</td> <td>name</td> </tr> <tr> <td>drawn</td> <td>19.01.09</td> <td>Burschik</td> </tr> <tr> <td>appd.</td> <td>19.01.09</td> <td>Schmidt</td> </tr> </table>				date	name	drawn	19.01.09	Burschik	appd.
		date	name								
	drawn	19.01.09	Burschik								
appd.	19.01.09	Schmidt									
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH			dwg no: <span style="float: right;">Inventor 10</span>								
			<b>43K1A837</b>								
			part no:								

