

Power Cord Adapter, NEMA 5-15R to NEMA L5-15P - Heavy-Duty, 15A, 120V, 14 AWG, 1 ft. (0.31 m), Black

MODEL NUMBER: P025-001









Heavy-duty extension cord converts a NEMA 5-15P plug into a locking NEMA L5-15P.

Features

Heavy-Duty Extension Cable for Network Devices That Require a Heavy-Gauge ConnectionThis 5-15R to L5-15R adapter features 14 AWG wire suitable for high power connections, making it a reliable solution for large server applications that require a higher-rated, heavier-gauge cable. It converts a standard NEMA 5-15P plug into a locking NEMA L5-15P plug, so it can connect to wall outlets, PDUs, surge protectors or UPS systems with NEMA L5-15R outlets. The 3-ft. (0.91 m) length helps reduce cable clutter and minimize the risk of tripping.

Locking L5-15R Connector Helps Prevent Accidental Disconnection and Expensive

DowntimeHaving a cable come loose accidentally can mean the loss of power and costly downtime. The locking NEMA L5-15R connector helps you avoid such danger, protecting critical equipment by maintaining a secure link without failure. The locking cable is also invaluable when moving equipment in a rack or removing equipment from tight areas, ensuring the power cord always stays connected.

Highlights

- Recommended for powering computers, servers and other network devices
- 1-ft. (0.31 m) length allows flexibility in placing devices, while avoiding cable clutter
- Heavy-duty power adapter replaces or upgrades standard cord provided by manufacturer
- Thick 14 AWG wire gauge manages high power levels required for larger equipment

Applications

- Connect devices like computers, servers and monitors to a PDU in your data center
- Extend an existing power connection up to 1-ft. (0.31 m) to more easily place a device or reach a power source in a rack
- Update or replace the standard power cord provided by a device's original manufacturer

Package Includes

 P025-001 5-15R to L5-15P Adapter Power Cord, 1-ft. (0.31 m), Black

Specifications

OVERVIEW		
UPC Code	037332185891	
Device Compatibility	Computer; Monitor/HDTV; Server; UPS; PDU	
Country/Region	North America	
INPUT		
Maximum Input Amps	15	
Voltage Compatibility (VAC)	120	



Plug Color Black			
Cable Jacket Color Black Cable Jacket Material PVC Cable Jacket Rating WV-1 Power Cod Jacket Type SJT Cable Outer Diameter (OD) 9.3mm Wire Gauge (AWC) 14 Wire Gauge (AWC) 14 Wire Gauge (OD - mm²) 2.08 Cable Length (It) 1 Cable Length (It) 0.30 Shipping Dimensions (Itwd / in.) 8.82 x 12.87 x 0.50 Shipping Dimensions (Itwd / in.) 8.82 x 12.87 x 0.50 Shipping Weight (Ibs.) 0.40 Shipping Weight (Ibs.) 0.48 Shipping Weight (Ibs.) Operating Temperature Range 14* to 140°F (-10° to 60°C) Operating Temperature Range 14* to 140°F (-10° to 60°C) Operating Humidity Range 35% to 85% RH, Non-Condensing Storage Humidity Range 35% to 85% RH, Non-Condensing CONNECTIONS Side 8 - Connector 1 NEMA 15-15P Side 8 - Connector 1 NEMA 15-15P Notaged Plug No Antibacterial No All yoldage No<	PHYSICAL		
Cable Jacket Material PVC Cable Jacket Rating VW-1 Power Cord Jacket Type SJT Cable Outer Diameter (OD) 9.3mm Number of Conductors 3 Wire Gauge (AWG) 14 Wire Gauge (AWG) 14 Cable Length (ft) 1 Cable Length (ft) 0.30 Shipping Dimensions (mvd / in.) 8.82 x 12.87 x 0.50 Shipping Dimensions (mvd / in.) 8.82 x 12.87 x 0.50 Shipping Weight (Ibs.) 0.40 Shipping Weight (Ibs.) 0.18 ENVIRONMENTAL Operating Temperature Range 14* to 140°F (-10° to 60°C) Storage Temperature Range 35% to 85% RH, Non-Condensing Storage Humidity Range 35% to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 NEMA L5-15P Side B - Connector 1 NEMA S-15R FFEATURES & SPECIFICATIONS Anilos Colled Power Cord No	Plug Color	Black	
Cable Jacket Raing VW-1 Power Cord Jacket Type SJT Cable Outer Diameter (OD) 9.3mm Number of Conductors 3 Wire Gauge (AWG) 14 Wire Gauge (OD - mm²) 2.08 Cable Length (ft.) 1 Cable Length (ft.) 1 Cable Length (m) 0.30 Shipping Dimensions (hwd / in.) 8.82 x 12.87 x 0.50 Shipping Dimensions (hwd / in.) 8.82 x 12.87 x 0.50 Shipping Dimensions (hwd / in.) 22.40 x 32.69 x 1.27 Shipping Weight (ibs.) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Deparating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range 35% to 85% RH, Non-Condensing Storage Humidity Range 35% to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 NEMA L5-15P NEMA 5-15R PEATURES & SPECIFICATIONS Antipled Plug No Locking Plug Yes Locking Plug	Cable Jacket Color	Black	
Power Cord Jacket Type	Cable Jacket Material	PVC	
Cable Outer Diameter (OD) Number of Conductors 3 Wire Gauge (AWG) 14 Wire Gauge (AWG) 14 Wire Gauge (OD - mm²) 2.08 Cable Length (Ith) 1 Cable Length (Im) 0.30 Shipping Dimensions (hwd / in.) 8.82 x 12.87 x 0.50 Shipping Dimensions (hwd / in.) 8.82 x 12.87 x 0.50 Shipping Weight (Ibs.) 0.40 Shipping Weight (Ibs.) 0.40 Shipping Weight (Ibs.) Coperating Temperature Range 14° to 140°F (-10° to 60°C) Deperating Humidity Range 35% to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 NEMA L5-15P Side B - Connector 1 NEMA 5-15R FEATURES & SPECIFICATIONS FEATURES & SPECIFICATIONS No Angled Plug No No Locking Plug Yes Cooled Power Cord No	Cable Jacket Rating	VW-1	
Number of Conductors 3 Wire Gauge (AWG) 14 Wire Gauge (AWG) 14 Wire Gauge (OD - mm²) 2.08 Cable Length (ft.) 1 Cable Length (m) 0.30 Shipping Dimensions (hwd / in.) 8.82 x 12.87 x 0.50 Shipping Dimensions (hwd / cm) 22.40 x 32.69 x 1.27 Shipping Weight (fbs.) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range 35% to 85% RH, Non-Condensing Storage Humidity Range 35% to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 NEMA L5-15P NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Lucking Plug Yes Colled Power Cord No	Power Cord Jacket Type	SJT	
Mire Gauge (AWG) 14 Mire Gauge (OD - mm²) 2.08 Cable Length (ft) 1 Cable Length (m) 0.30 Shipping Dimensions (hwd / in.) 8.82 x 12.87 x 0.50 Shipping Dimensions (hwd / cm) 22.40 x 32.69 x 1.27 Shipping Weight (lbs.) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range 35% to 85% RH, Non-Condensing Storage Humidity Range 35% to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 NEMA L5-15P Side B - Connector 1 NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Locking Plug Yes Coiled Power Cord No	Cable Outer Diameter (OD)	9.3mm	
September Sept	Number of Conductors	3	
Cable Length (ft.) Cable Length (m) Cable Length (m) O.30 Shipping Dimensions (hwd / in.) S.82 x 12.87 x 0.50 Shipping Dimensions (hwd / cm) 22.40 x 32.69 x 1.27 Shipping Weight (lbs.) O.40 Shipping Weight (kg) O.18 ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range 14° to 140°F (-10° to 60°C) Operating Humidity Range 35% to 85% RH, Non-Condensing Storage Humidity Range 35% to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 NEMA L5-15P NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Cocking Plug Yes Colled Power Cord No	Wire Gauge (AWG)	14	
Cable Length (m) 0.30 Shipping Dimensions (hwd / in.) 8.82 x 12.87 x 0.50 Shipping Dimensions (hwd / cm) 22.40 x 32.69 x 1.27 Shipping Weight (lbs.) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range 14° to 140°F (-10° to 60°C) Operating Humidity Range 35% to 85% RH, Non-Condensing Storage Humidity Range 35% to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 NEMA L5-15P NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No Locking Plug Yes Colled Power Cord No	Wire Gauge (OD - mm²)	2.08	
Shipping Dimensions (hwd / in.) 8.82 x 12.87 x 0.50 Shipping Dimensions (hwd / cm) 22.40 x 32.69 x 1.27 Shipping Weight (lbs.) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range 14° to 140°F (-10° to 60°C) Operating Humidity Range 35% to 85% RH, Non-Condensing Storage Humidity Range 35% to 85% RH, Non-Condensing CONNECTIONS Side A · Connector 1 NEMA L5-15P NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No Locking Plug Yes Coiled Power Cord No	Cable Length (ft.)	1	
Shipping Dimensions (hwd / cm) 2.40 x 32.69 x 1.27 Shipping Weight (lbs.) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range 14° to 140°F (-10° to 60°C) Operating Humidity Range 35% to 85% RH, Non-Condensing Storage Humidity Range 35% to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 NEMA L5-15P NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Locking Plug Yes Coiled Power Cord No	Cable Length (m)	0.30	
Shipping Weight (lbs.) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range 14° to 140°F (-10° to 60°C) Operating Humidity Range 35% to 85% RH, Non-Condensing Storage Humidity Range 35% to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 NEMA L5-15P Side B - Connector 1 NEMA 5-15R FEATURES & SPECIFICATIONS Angled Plug No High Voltage No Locking Plug Yes Coiled Power Cord No	Shipping Dimensions (hwd / in.)	8.82 x 12.87 x 0.50	
Shipping Weight (kg) ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range 14° to 140°F (-10° to 60°C) Operating Humidity Range 35% to 85% RH, Non-Condensing Storage Humidity Range 35% to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 NEMA L5-15P NEMA 5-15R FEATURES & SPECIFICATIONS Angled Plug No High Voltage No Locking Plug Yes Coiled Power Cord No	Shipping Dimensions (hwd / cm)	22.40 x 32.69 x 1.27	
ENVIRONMENTAL Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range 14° to 140°F (-10° to 60°C) Operating Humidity Range 35% to 85% RH, Non-Condensing Storage Humidity Range 35% to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 NEMA L5-15P Side B - Connector 1 NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No Locking Plug Yes Coiled Power Cord No	Shipping Weight (lbs.)	0.40	
Operating Temperature Range 14° to 140°F (-10° to 60°C) Storage Temperature Range 14° to 140°F (-10° to 60°C) Operating Humidity Range 35% to 85% RH, Non-Condensing Storage Humidity Range 35% to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 NEMA L5-15P Side B - Connector 1 NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Locking Plug Yes Coiled Power Cord No	Shipping Weight (kg)	0.18	
Storage Temperature Range 14° to 140°F (-10° to 60°C) Operating Humidity Range 35% to 85% RH, Non-Condensing Storage Humidity Range 35% to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 NEMA L5-15P Side B - Connector 1 NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Locking Plug Yes Coiled Power Cord No	ENVIRONMENTAL		
Operating Humidity Range 35% to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 NEMA L5-15P Side B - Connector 1 NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Locking Plug Yes Coiled Power Cord No	Operating Temperature Range	14° to 140°F (-10° to 60°C)	
Storage Humidity Range 35% to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 NEMA L5-15P Side B - Connector 1 NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Locking Plug Yes Coiled Power Cord No	Storage Temperature Range	14° to 140°F (-10° to 60°C)	
CONNECTIONS Side A - Connector 1 NEMA L5-15P Side B - Connector 1 NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Locking Plug Yes Coiled Power Cord No	Operating Humidity Range	35% to 85% RH, Non-Condensing	
Side A - Connector 1 NEMA L5-15P NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Locking Plug Yes Coiled Power Cord NEMA L5-15P NEMA 5-15R	Storage Humidity Range	35% to 85% RH, Non-Condensing	
Side B - Connector 1 NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage Locking Plug Yes Coiled Power Cord No	CONNECTIONS		
FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Locking Plug Yes Coiled Power Cord No	Side A - Connector 1	NEMA L5-15P	
Antibacterial No Angled Plug No High Voltage No Locking Plug Yes Coiled Power Cord No	Side B - Connector 1	NEMA 5-15R	
Angled Plug No High Voltage No Locking Plug Yes Coiled Power Cord No	FEATURES & SPECIFICATIONS		
High Voltage No Locking Plug Yes Coiled Power Cord No	Antibacterial	No	
Locking Plug Yes Coiled Power Cord No	Angled Plug	No	
Coiled Power Cord No	High Voltage	No	
	Locking Plug	Yes	
STANDARDS & COMPLIANCE	Coiled Power Cord	No	
	STANDARDS & COMPLIANCE		
Product Certifications cUL Listed; UL Listed	Product Certifications	cUL Listed; UL Listed	



Product Compliance	RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.